



TECHNICAL DATA SHEET

SURVEY MARKING PAINT

Description

EAL Professional Survey Marking Paint is a quick drying survey and spot marking paint for use in a range of applications including construction, roadworks, surveying, landscaping and civil works. Unique upside down nozzle and spray through cap for inverted marking.

Suitable for use on almost any surface including:

- Bitumen
- Concrete
- Grass
- Soil
- Steel
- Timber
- Rock
- Gravel

Typical Properties

Size	350g Aerosol
Appearance	Standard & Fluoro Colours
Drying Time	Approx. 5 minutes
Solvent	Liquid Hydrocarbon
Propellant	Dimethylether
UN No.	1950
DG Class	2.1

Directions for Use

Shake can vigorously for at least 20 seconds. Hold can in an inverted position at a distance of 15-20cms from the surface and depress button on cap to activate aerosol. After use hold can upright and spray for 1 second to clear nozzle.

For safe handling information please see Safety Data Sheet (SDS).



The data contained herein is offered in good faith based upon information that is believed to be accurate and reliable, but no warranty, express or implied, regarding the accuracy of such information is made. The conditions or methods of handling, storage, use and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. It is the responsibility of the user to determine this products suitability for their intended purpose.

Engineering Adhesives & Lubricants (Aust) Pty Ltd

Tel: (07) 5531-4242 | Fax: (07) 5531-4243

Email: info@eal.com.au

Website: www.eal.com.au



www.eal.com.au