



PRODUCT DATA SHEET

ZINC GAL®

DESCRIPTION

EAL ZINC GAL® is a heavy duty, zinc-rich primer that provides long term protection to iron and steel. The cathodic (galvanic) action between the ferrous metal and the metallic zinc forms a sacrificial protective barrier against corrosion.

EAL ZINC GAL® contains a high concentration of very fine particles of 98.5% pure zinc with 91.4% zinc in the dry film. **Conforms to the requirements of AS/NZS 3750:9, paints for steel structures.**

TYPICAL APPLICATIONS

- Restoration of galvanized steel roofing
- Agricultural machinery
- Mining equipment, oil rigs and off-shore drilling structures
- Underground pipe lines, ducts, automotive bodies
- Fences & gates
- Air conditioning units
- Railroad equipment, structural steel tanks, transmission towers
- Repairing welds and previously galvanized surfaces

TYPICAL PROPERTIES

Colour	Grey
Density, g/ml	1.37
VOC Content	370g/L 34.9% wt
Coverage	Up to 2 sq mtrs per 400g can
Drying Time @ 25°C	5-10 min

DIRECTIONS FOR USE

1. Surface to be treated must be totally free of rust, dirt, oil etc. If necessary sandblast or clean with sandpaper.
2. Shake can vigorously until agitator ball is free and continue shaking thereafter for a further 1 minute.
3. Holding can upright, spray \pm 20cm away from surface using smooth even strokes. To prevent paint running or sagging do not spray too heavily or too close to the surface. Repeat as necessary allowing time for drying between each coat.
4. May be painted over once dry to provide a final protective top coat.





PRODUCT DATA SHEET

ZINC GAL®

HANDLING AND STORAGE

- Store under cover below 50°C and away from direct sunlight.
- Contents under pressure.
- Do not smoke.
- Do not puncture or incinerate can, even when empty.
- Keep out of reach of children.
- Read directions on product label before use.

For additional safe handling information please see Safety Data Sheet (SDS).

PACKAGING

400g Aerosol
12 x 400g cans per carton
Part No. ZGAL400

NOTE

The data contained herein is offered in good faith based upon information that is believed to be accurate and reliable, but no warranty, express or implied, regarding the accuracy of such information is made. The conditions or methods of handling, storage, use and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. It is the responsibility of the user to determine the products suitability for their intended purpose.

CONTACT US

Engineering Adhesives & Lubricants (Aust)
Pty Ltd

Tel: (07) 5531-4242 | Fax: (07) 5531-4243

Email: info@eal.com.au

Website: www.eal.com.au