

Safety Data Sheet

Clear Silicone Adhesive/Sealant

Section 1. Identification

Product Identifier Clear Silicone Adhesive/Sealant

Synonyms 49204, 49294

Manufacturer Stock Numbers 143372, 143400

Recommended use Refer to Technical Information

Uses advised against Refer to Technical Information

Supplier Contact

Address

Engineering Adhesives & Lubricants (Aust) Pty Ltd
3/119 Olympic Circuit
Southport QLD 4215

Phone

(07) 5531-4242

Emergency Phone

131126

Poisons Information
Centre

Fax

(07) 5531-4243

Section 2. Hazards Identification

Classification N/A

Signal Word

Pictogram

Hazard Statements None needed according to classification criteria

Precautionary Statements

Response N/A

Prevention Use only outdoors or in a well-ventilated area.

Storage N/A

Disposal N/A

Ingredients of unknown toxicity 0%

Hazards not Otherwise Classified

GHS Label Element Not a hazardous substance or mixture.

GHS Classification Not a hazardous substance or mixture.

Section 3. Ingredients

CAS	Ingredient Name	Weight %
17689-77-9	Ethyltriacetoxysilane	1% - 5%
4253-34-3	Methyltriacetoxysilane	1% - 5%

Occupational exposure limits, if available, are listed in Section 8.

Section 4. First-Aid Measures

Eye Contact Immediately flush with water for 15 minutes. Seek medical attention.

Skin Contact Remove from skin and wash thoroughly with soap and water or waterless cleanser. Get medical attention if irritation or other ill effects develop or persist.

Inhalation Material is not likely to present an inhalation hazard at ambient conditions. If material is heated or vapor are generated, care should be taken to prevent inhalation. In case of exposure to vapor, move to fresh air.

Ingestion No first aid should be needed.

Comments Treat according to person's condition and specifics of exposure.

Section 5. Fire Fighting Measures

Suitable Extinguishing Media On large fires use dry chemical, foam, or water spray. On small fires use carbon dioxide, dry chemical or water spray. Water can be used to cool fire exposed containers.

Unsuitable Extinguishing Media None known

Hazardous Decomposition Products Thermal breakdown of this product during fire or very high heat conditions may evolve the following hazardous decomposition products:
Carbon oxides and traces of incompletely burned carbon compounds
Formaldehyde
Silicon dioxide

Unusual Fire or Explosion Hazards None known

Special Fire Fighting Procedures Self-contained breathing apparatus and protective clothing should be worn when fighting large fires involving chemicals. Determine the need to evacuate or isolate the area according to your local emergency plan. Use water spray to keep fire exposed containers cool.

Comment

When temperatures above 150C in the presence of air, product can form formaldehyde vapors. Formaldehyde is a potential cancer hazard, a known skin and respiratory sensitizer, and an irritant to the eyes, nose, throat, skin and digestive system. Safe handling conditions may be maintained by keeping vapor concentrations within the OSHA Permissible Exposure Limits for formaldehyde.

Section 6. Accidental Release Measures

Steps to be taken in case of spill or release

Observe all personal protection equipment recommendations. Wipe up or scrape up and contain for salvage or disposal. Clean area as appropriate since spilled materials, even in small quantities, may present a slip hazard. Final cleaning may require steam, solvents or detergents. Dispose of saturated absorbant or cleaning materials appropriately, since spontaneous heating may occur.

Local, state and federal laws and regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which federal, state and local laws and regulations are applicable. Sections 13 and 15 of this MSDS provide information regarding certain federal and state requirements.

Section 7. Handling and Storage

Storage

Use reasonable care and store away from oxidizing materials. Keep container closed and store away from water or moisture.

Handling

Use with adequate ventilation. Product evolves acetic acid with exposed to water or humid air. Provide ventilation during use to control acetic acid with exposure guidelines or use respiratory protection. Avoid eye contact. Avoid skin contact. Do not take internally. Avoid breathing vapor. Keep container closed.

Section 8. Exposure Controls/Personal Protection

Occupational Exposure Limits

Ingredient Name	ACGIH TLV	OSHA PEL	STEL
Ethyltriacetoxysilane	TWA 10ppm	TWA 10ppm	15ppm
Methyltriacetoxysilane	TWA 10ppm	TWA 10ppm	15ppm

Personal Protective Equipment

Goggles, Gloves

Engineering Controls

Local Ventilation: Recommended
General Ventilation: Recommended

Eye Protection

Use proper protection - safety glasses as a minimum.

Skin Protection

Wash at mealtimes and end of shift. Contaminated clothing and shoes should be removed as soon as practical and thoroughly cleaned before reuse. Chemical protective gloves are recommended.

Suitable Gloves:

Handle in accordance with good industrial hygiene and safety practices.

Respiratory Protection

Use respiratory protection unless adequate exhaust ventilation is provided or exposure assessment demonstrates that exposures are within exposure guidelines. Industrial Hygiene Personnel can assist in judging the adequacy of existing engineering controls.

Suitable Respirator

Respiratory protection is not needed under ambient conditions. If vapor is generated when material is heated or handled, the following is advised. General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. The following Australian Standards will provide general advice regarding respiratory equipment: **AS/NZS 1715**.

Precautionary Measures

Avoid eye contact. Avoid skin contact. Avoid breathing vapor. Keep container closed. Do not take internally. Use reasonable care.

Comment

Product evolves acetic acid when exposed to water or humid air. Provide ventilation during use to control acetic acid within exposure guidelines or use respiratory protection.

Note

When heated to temperatures above 150C (300F) in the presence of air, product can form formaldehyde vapors. Physical and health hazard information is readily available on the Material Safety Data Sheet.

These precautions are for room temperature handling. Use at elevated temperatures or aerosol/spray applications may require added precautions.

Section 9. Physical and Chemical Properties

Physical State	Paste
Color	Clear
Odor	Acetic Acid Odor
Odor Threshold	N/A
Solubility	Not Determined
Partition coefficient Water/n-octanol	N/A
VOC%	23 g/L
Viscosity	Not Determined
Specific Gravity	1.007
Density lbs/Gal	N/A
Pounds per Cubic Foot	N/A
Flash Point	>212F / >100C
FP Method	Closed Cup

pH	Not Determined
Melting Point	Not Determined
Boiling Point	Not Determined
Boiling Range	N/A
LEL	N/A
UEL	N/A
Evaporation Rate	Not Determined
Flammability	N/A
Decomposition Temperature	N/A
Auto-ignition Temperature	N/A
Vapor Pressure	Not Determined
Vapor Density	Not Determined

Note The above information is not intended for use in preparing product specifications.

Section 10. Stability and Reactivity

Chemical Stability	Stable
Hazardous polymerization	Will not occur
Conditions to avoid	None known
Materials to Avoid / Incompatibility	Oxidizing material can cause a reaction. Water, moisture or humid air can cause hazardous vapors to form as described in Section 8.

Section 11. Toxicological Information

Special Hazard Information on Components No known applicable information.

Component Toxicology Information No known applicable information.

Section 12. Ecological Information

Fate and Effects in Waste Water Treatment Plants	Complete information is not yet available.
Environmental Effects	Complete information is not yet available.
Environmental Fate and Distribution	Complete information is not yet available.

Section 13. Disposal

Waste Disposal Method We make no guarantee or warranty of any kind that the use or disposal of this product complies with all local, state, or federal laws. It is also the obligation of each user of the product mentioned herein to determine and comply with the requirements of all applicable statutes.

Disposal of unused portions of this product and process waste containing this product should be done only after a careful evaluation and in compliance with all federal, local and state laws.

Section 14. Transport Information

UN Number	N/A
UN Proper Shipping Name	Not regulated
ADG Classification	Not regulated
Packing Group	Not regulated
Air Shipment (IATA)	Not subject to IATA regulations.
Ocean Shipment (IMDG)	Not subject to IMDG code.

Section 15. Regulatory Information

AICS All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16. Other Information

Revision Date 30/05/2018

Disclaimer The data contained herein is based upon information that Engineering Adhesives & Lubricants (Aust) Pty Ltd believes to be reliable. Users of this product have the responsibility to determine that suitability of use and to adopt all necessary precautions to ensure the safety and protection of property and persons involved in said use. All statements or suggestions are made without warranty, expressed or implied, regarding the accuracy of the information, the hazards connected with the use of the material or the results to be obtained from the use thereof.