



www.eal.com.au

Product Name: Cybercryl 1326
Page: 1 of 5
This revision issued: April, 2013

Section 1 - Identification of The Material and Supplier

Engineering Adhesives & Lubricants (Aust) Pty Ltd
Unit 3/119 Olympic Circuit
Southport, Qld 4215

Tel: (07) 5531-4242
Fax: (07) 5531-4243
Email: info@eal.com.au

Chemical nature: Modified acrylic.
Trade Name: **Cybercryl 1326**
Product Use: Adhesive.
Creation Date: **April, 2013**
This version issued: **April, 2013** and is valid for 5 years from this date.

Section 2 - Hazards Identification

Statement of Hazardous Nature

This product is classified as: Xi, Irritating. Hazardous according to the criteria of SWA.

Not a Dangerous Good according to the Australian Dangerous Goods (ADG) Code. However, this is a C1 Combustible Liquid so must be stored and handled as specified in AS 1940 "The storage and handling of flammable and combustible liquids."

Risk Phrases: R43, R36/37/38. May cause sensitisation by skin contact. Irritating to eyes, respiratory system and skin.

Safety Phrases: S23, S26, S28, S38, S24/25, S37/39. Do not breathe vapours or mists. In case of contact with eyes, rinse immediately with plenty of water and contact a doctor or Poisons Information Centre. After contact with skin, wash immediately with plenty of soap and water. In case of insufficient ventilation, wear suitable respiratory equipment. Avoid contact with skin and eyes. Wear suitable gloves and eye/face protection.

SUSMP Classification: None allocated.

ADG Classification: None allocated. Not a Dangerous Good under the ADG Code.

UN Number: None allocated



GHS Signal word: WARNING

HAZARD STATEMENT:

- H227: Combustible liquid.
- H315: Causes skin irritation.
- H317: May cause an allergic skin reaction.
- H320: Causes eye irritation.
- H335: May cause respiratory irritation.

PREVENTION

- P102: Keep out of reach of children.
- P261: Avoid breathing fumes, mists, vapours or spray.
- P264: Wash contacted areas thoroughly after handling.
- P271: Use only outdoors or in a well ventilated area.
- P272: Contaminated work clothing should not be allowed out of the workplace.
- P280: Wear protective gloves, protective clothing and eye or face protection.

RESPONSE

- P312: Call a POISON CENTRE or doctor if you feel unwell.
- P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
- P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.
- P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P332+P313: If skin irritation occurs: Get medical advice.

MATERIAL SAFETY DATA SHEET

Issued by: Engineering Adhesives & Lubricants (Aust) Pty Ltd Phone: 07 5531 4242 (business hours)
Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

P337+P313: If eye irritation persists: Get medical advice.
P391: Collect spillage.
P370+P378: In case of fire, use carbon dioxide, dry chemical, foam.

STORAGE

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

DISPOSAL

P501: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

Emergency Overview

Physical Description & Colour: Amber liquid.

Odour: Sharp, pungent odour.

Major Health Hazards: irritating to eyes, respiratory system and skin, possible skin sensitiser.

Emergency Overview

Persons sensitised to 2-hydroxyethyl methacrylate should avoid contact with this product.

Inhalation:

Short Term Exposure: Available data indicates that this product is not harmful. However product is an inhalation irritant. Symptoms may include headache, irritation of nose and throat and increased secretion of mucous in the nose and throat. Other symptoms may also become evident, but they should disappear after exposure has ceased.

Long Term Exposure: No data for health effects associated with long term inhalation.

Skin Contact:

Short Term Exposure: Classified as a potential sensitiser by skin contact. Exposure to a skin sensitiser, once sensitisation has occurred, may manifest itself as skin rash or inflammation, and in some individuals this reaction can be severe. In addition product is a skin irritant. Symptoms may include itchiness and reddening of contacted skin. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term skin exposure.

Eye Contact:

Short Term Exposure: This product is an eye irritant. Symptoms may include stinging and reddening of eyes and watering which may become copious. Other symptoms may also become evident. If exposure is brief, symptoms should disappear once exposure has ceased. However, lengthy exposure or delayed treatment may cause permanent damage.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product is an oral irritant. Symptoms may include burning sensation and reddening of skin in mouth and throat. Other symptoms may also become evident, but all should disappear once exposure has ceased.

Long Term Exposure: No data for health effects associated with long term ingestion.

Carcinogen Status:

SWA: No significant ingredient is classified as carcinogenic by SWA.

NTP: No significant ingredient is classified as carcinogenic by NTP.

IARC: Acrylic Acid is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

Section 3 - Composition/Information on Ingredients

Ingredients	CAS No	Conc,%	TWA (mg/m ³)	STEL (mg/m ³)
Methacrylate Monomer	secret	30-60	not set	not set
High Boiling Point Methacrylate	secret	10-30	not set	not set
Acrylic acid	79-10-7	1-5	5.9	not set
2-hydroxyethyl methacrylate	868-77-9	10-30	not set	not set

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak" is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

MATERIAL SAFETY DATA SHEET

Issued by: Engineering Adhesives & Lubricants (Aust) Pty Ltd Phone: 07 5531 4242 (business hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 4 - First Aid Measures

General Information:

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 1126 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this MSDS with you when you call.

Inhalation: If irritation occurs, contact a Poisons Information Centre, or call a doctor. Remove source of contamination or move victim to fresh air. If breathing is difficult, oxygen may be beneficial if administered by trained personnel, preferably on a doctor's advice. In severe cases, symptoms of pulmonary oedema can be delayed up to 48 hours after exposure.

Skin Contact: Wash gently and thoroughly with warm water (use non-abrasive soap if necessary) for 10-20 minutes or until product is removed. Under running water, remove contaminated clothing, shoes and leather goods (e.g. watchbands and belts) and completely decontaminate them before reuse or discard. If irritation persists, repeat flushing and seek medical attention.

Eye Contact: Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 20 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

Ingestion: If swallowed, do NOT induce vomiting. Wash mouth with water and contact a Poisons Information Centre, or call a doctor.

Section 5 - Fire Fighting Measures

Fire and Explosion Hazards: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. This product is classified as a C1 combustible product. There is no risk of an explosion from this product under normal circumstances if it is involved in a fire. Violent steam generation or eruption may occur upon application of direct water stream on hot liquids.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

Extinguishing Media: In case of fire, use carbon dioxide, dry chemical, foam.

Fire Fighting: If a significant quantity of this product is involved in a fire, call the fire brigade.

Flash point: >93°C, Closed cup

Upper Flammability Limit: No data.

Lower Flammability Limit: No data.

Autoignition temperature: No data.

Flammability Class: C1

Section 6 - Accidental Release Measures

Accidental release: This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

Section 7 - Handling and Storage

Handling: Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this MSDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

Storage: Note that this product is combustible and therefore, for Storage, meets the definition of Dangerous Goods in some states. If you store large quantities (tonnes) of such products, we suggest that you consult your state's Dangerous Goods authority in order to clarify your obligations regarding their storage.

Store packages of this product in a cool place. Make sure that containers of this product are kept tightly closed. Keep containers dry and away from water. Keep containers of this product in a well ventilated area. Make sure that the product does not come into contact with substances listed under "Incompatibilities" in Section 10. Some liquid preparations settle or separate on standing and may require stirring before use. Check packaging - there may be further storage instructions on the label.

MATERIAL SAFETY DATA SHEET

Issued by: Engineering Adhesives & Lubricants (Aust) Pty Ltd Phone: 07 5531 4242 (business hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 8 - Exposure Controls and Personal Protection

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m ³)	STEL (mg/m ³)
Acrylic acid	5.9	not set

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

Ventilation: This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

Eye Protection: Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

Skin Protection: If you believe you may have a sensitisation to this product or any of its declared ingredients, you should prevent skin contact by wearing impervious gloves, clothes and, preferably, apron. Make sure that all skin areas are covered. See below for suitable material types.

Protective Material Types: We suggest that protective clothing be made from the following materials: neoprene.

Respirator: Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above.

Eyebaths or eyewash stations and safety deluge showers should be provided near to where this product is being handled commercially.

Section 9 - Physical and Chemical Properties:

Physical Description & colour:	Amber liquid.
Odour:	Sharp, pungent odour.
Boiling Point:	> 150°C at 100kPa
Freezing/Melting Point:	No specific data. Liquid at normal temperatures.
Volatiles:	No specific data. VOC 25.8%, 284 grams/litre (EPA Method 24)
Vapour Pressure:	< 1.32 kPa at 25°C
Vapour Density:	No data.
Specific Gravity:	1.11 at 25°C
Water Solubility:	Slightly soluble.
pH:	No data.
Volatility:	No data.
Odour Threshold:	No data.
Evaporation Rate:	No data.
Coeff Oil/water Distribution:	No data
Autoignition temp:	No data.

Section 10 - Stability and Reactivity

Reactivity: This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

Conditions to Avoid: This product should be kept in a cool place, preferably below 30°C. Keep containers tightly closed. Containers should be kept dry. Keep containers and surrounding areas well ventilated.

Incompatibilities: Polymerized by contact with oxidizers, amines, and alkalis..

Fire Decomposition: Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

Polymerisation: This product may undergo polymerisation in the presence of certain chemical reagents. See Incompatibilities above. Polymerisation is often accompanied by liberation of heat, and may lead to a dangerous or explosive situation. If the product is seen to be heating up, treat as a fire incident.

MATERIAL SAFETY DATA SHEET

Issued by: Engineering Adhesives & Lubricants (Aust) Pty Ltd Phone: 07 5531 4242 (business hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)

Section 11 - Toxicological Information

Local Effects:

Target Organs: There is no data to hand indicating any particular target organs.

2-hydroxyethyl Methacrylate is Classed by SWA as a potential sensitiser by skin contact.

Classification of Hazardous Ingredients

Ingredient	Risk Phrases
Acrylic Acid	$\geq 1\%$ Conc $< 5\%$: Xi; R36/37/38
2-hydroxyethyl Methacrylate	Conc $\geq 20\%$: Xi; R36/38; R43

Section 12 - Ecological Information

Insufficient data to be sure of status.

Section 13 - Disposal Considerations

Disposal: Dispose of small quantities and empty containers by wrapping with paper and putting in garbage. For larger quantities, if recycling or reclaiming is not possible, use a commercial waste disposal service.

Section 14 - Transport Information

ADG Code: This product is not classified as a Dangerous Good. No special transport conditions are necessary unless required by other regulations.

Section 15 - Regulatory Information

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

Section 16 - Other Information

This MSDS contains only safety-related information. For other data see product literature.

Acronyms:

ADG Code	Australian Code for the Transport of Dangerous Goods by Road and Rail (7 th edition)
AICS	Australian Inventory of Chemical Substances
SWA	Safe Work Australia, formerly ASCC and NOHSC
CAS number	Chemical Abstracts Service Registry Number
Hazchem Code	Emergency action code of numbers and letters that provide information to emergency services especially firefighters
IARC	International Agency for Research on Cancer
NOS	Not otherwise specified
NTP	National Toxicology Program (USA)
R-Phrase	Risk Phrase
SUSMP	Standard for the Uniform Scheduling of Medicines & Poisons
UN Number	United Nations Number

THIS MSDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD STATEMENT: INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS MSDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS. OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

This MSDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (December 2011)
Copyright © Kilford & Kilford Pty Ltd, April, 2013.

<http://www.kilford.com.au> Phone (02)9251 4532

MATERIAL SAFETY DATA SHEET

Issued by: Engineering Adhesives & Lubricants (Aust) Pty Ltd Phone: 07 5531 4242 (business hours)

Poisons Information Centre: 13 1126 from anywhere in Australia, (0800 764 766 in New Zealand)