TREBLEX

Solutions for industry

PRODUCT DATA SHEET

Product Code: TCCNF

NON-FLAMMABLE CONTACT CLEANER

DESCRIPTION

TREBLEX Non Flammable Contact Cleaner is a technically superior. stable, inert high purity cleaning solvent suitable for use in all electrical and electronic applications. This product has **NO FLASH POINT**, is **NON FLAMMABLE**, and contains no lubricants.

FEATURES

- 360° valve, use inverted if needed.
- Non Flammable, no flash point.
- Chemically stable, non corrosive and non conductive.
- Contains no methyl chloroform or CFC 113.
- Fast evaporating highly refined solvents, leaves no residue.

- Superior non staining cleaning solvent.
- Helps prevent contact failure by dissolving and flushing away contaminants.
- Instantly removes grease, oil, dirt, flux and other potential contaminants.
- · Rapid and complete evaporation.

APPLICATIONS

When used as directed TREBLEX Non Flammable Contact Cleaner can be used for the following applications:

- Any switch contacts
- Terminal blocks
- Air conditioning
- Connecters
- · Motor controls and housings
- Chargers
- Refrigeration
- Fans

- Motor shafts.
- All milling applications
- All mining applications
- All off shore oil and gas operations
- Fork trucks
- All battery powered vehicles
- · Circuit boards
- Alarms

DIRECTIONS

- Shake can well before use.
- · Apply evenly to surface requiring cleaning.
- Allow product to flush contaminants away.
- Use an abrasive to remove oxidation from contact surfaces.
- Burnishing is also an option.
- Caution must be used with regard to plastics, test on a small part first.

Size: 450g Cartons of 12

 ${\sf SAFETY}: {\sf Classified\ as\ hazardous.\ Please\ read\ SDS\ sheet\ before\ use.\ Keep\ out\ of\ reach\ of\ children.}$

Treblex Industrial Pty Ltd : U1/26 ilda Rd, Canning Vale, WA, 6155 — Ph: 08 9456 5825

Email: sales@treblex.com.au Website: www.treblex.com.au

Information contained herein is accurate at the time of writing this document. However specifications change from time to time, please ensure that the specifications meet your requirements.

