



www.eal.com.au

PRODUCT DATA SHEET

FAST DRY ENAMELS

DESCRIPTION

EAL FAST DRY ENAMELS are industrial quality spray paints designed for interior and exterior use. Typically used on industrial fittings, doors, gates, wrought iron, screens and factory equipment, in fact anywhere that a high quality finish is required.

SURFACE PREPARATION

Surface must be free of dust, wax, and rust. All bare timber should be undercoated and bare metal primed with metal primer. Newspapers or plastic drop sheets should be spread around the work area to protect from over spray.

Shake the can thoroughly to mix the paint for one minute to ensure an even result.

Adjust the spray pattern: The fanjet may be adjusted for horizontal or vertical spraying (see back of can for details).

TYPICAL PROPERTIES

Physical Description and Colour	Liquid - in aerosol form
Temperature Resistance	Up to 120°C
Coverage	Up to 2.3 square metres per 350g can
Drying Time @ 25°C	10-15 min

SPECIAL FEATURES

- Fast Drying
- Industrial Quality
- Hard Wearing
- High Gloss (excepting matt & primer)

DIRECTIONS FOR USE

Hold the can approx. 20-30 cms from the surface. Depress valve head (button) and spray with smooth even strokes horizontally and then vertically, applying several light coats rather than one heavy coat to achieve best results. If a second coat is required, allow the first coat to dry for 10-15 minutes before re-coating.





www.eal.com.au

PRODUCT DATA SHEET

FAST DRY ENAMELS

COLOUR RANGE

EAL Fast Dry Enamels are available in the following colours:

-  Black Gloss
-  Black Matt
-  Mid Blue
-  Ocean Blue
-  Brunswick Green
-  Grey Primer
-  Signal Red
-  Silver
-  White Gloss
-  Golden Yellow
-  International Orange

(Approximate colours only)

HANDLING AND STORAGE

- Store under cover below 50°C and away from direct sunlight.
- Contents under pressure.
- Do not smoke.
- Do not puncture or incinerate can, even when empty.
- Keep out of reach of children.
- Read directions on product label before use.

For additional safe handling information please see [Safety Data Sheet \(SDS\)](#).

NOTE

The data contained herein is offered in good faith based upon information that is believed to be accurate and reliable, but no warranty, express or implied, regarding the accuracy of such information is made. The conditions or methods of handling, storage, use and disposal of this product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of this product. It is the responsibility of the user to determine the products suitability for their intended purpose.

CONTACT

Engineering Adhesives & Lubricants (Aust)
Pty Ltd
Tel: (07) 5531-4242 | Fax: (07) 5531-4243
Email: info@eal.com.au
Website: www.eal.com.au

