



Safety Data Sheet according to WHS Regulations

Printing date 07.05.2021 Version number 32 Revision: 13.04.2021

1 Identification

- Product identifier

- Trade name: Vibra-TITE® VC-3®

- Article number: VC-3

- Relevant identified uses of the substance or mixture and uses advised against

No further relevant information available.

- Sector of Use SU3 Industrial uses: Uses of substances as such or in preparations at industrial sites

- Product category PC1 Adhesives, sealants

- Process category

PROC8b Transfer of substance or mixture (charging and discharging) at dedicated facilities

PROC10 Roller application or brushing

PROC13 Treatment of articles by dipping and pouring

- Environmental release category ERC5 Use at industrial site leading to inclusion into/onto article

- Article category AC0 Other

- Technical function No technical function

- Application of the substance / the mixture Thread Locking

- Details of the supplier of the safety data sheet

- Manufacturer: Supplier:

ND Industries, Inc Engineering Adhesives & Lubricants (Aust) Pty Ltd 1000 North Crooks Road

Unit 3, 119 Olympic Circuit

Clawson, MI 48017 Southport, QLD 4215

USA Australia

Telephone: +1-248-288-0000 Telephone: +61 (07) 5531-4242 Email: info@ndindustries.com Email: info@eal.com.au Website: www.ndindustries.com Website: www.eal.com.au

- Further information obtainable from: Product Safety Department

- Emergency telephone number: United States: 1-800-424-9300 International: +1-703-527-3887

2 Hazard(s) Identification

Classification of the substance or mixture



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

STOT SE 3 H336 May cause drowsiness or dizziness.

- Label elements

GHS label elements The product is classified and labelled according to the Globally Harmonised System (GHS).

Hazard pictograms





GHS02 GHS07

- Signal word Danger

- Hazard-determining components of labelling:

methyl ethyl ketone

- Hazard statements

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Precautionary statements

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P233 Keep container tightly closed.

P241 Use explosion-proof [electrical/ventilating/lighting] equipment.

(Contd. of page 1)

Safety Data Sheet according to WHS Regulations

Printing date 07.05.2021 Version number 32 Revision: 13.04.2021

Trade name: Vibra-TITE® VC-3®

P261 Avoid breathing dust/fume/gas/mist/vapours/spray.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

- Other hazards

- Results of PBT and vPvB assessment

- **PBT:** Not applicable.
- vPvB: Not applicable.

3 Composition and Information on Ingredients

- Chemical characterisation: Mixtures

- Description: Mixture of substances listed below with nonhazardous additions.

Dangerous components:

CAS: 78-93-3 methyl ethyl ketone

Flam. Liq. 2, H225; Eye Irrit. 2, H319; STOT SE 3, H336

60 - 69%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

4 First Aid Measures

- Description of first aid measures

- After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- After eye contact: Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- After swallowing: If symptoms persist consult doctor.
- Information for doctor:
 - Most important symptoms and effects, both acute and delayed No further relevant information available.
 - Indication of any immediate medical attention and special treatment needed
 No further relevant information available.

5 Fire Fighting Measures

- Extinguishing media
 - Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 - For safety reasons unsuitable extinguishing agents: Water
- Special hazards arising from the substance or mixture No further relevant information available.
- Advice for firefighters
 - Protective equipment:

Wear self-contained respiratory protective device.

Wear fully protective suit.

6 Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation

Wear protective clothing.

- Environmental precautions: Do not allow to enter sewers/ surface or ground water.
- Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Ensure adequate ventilation.

Do not flush with water or aqueous cleansing agents

Dispose of the material collected according to regulations.

- Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- Handling:

Precautions for safe handling

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

No special precautions are necessary if used correctly.

- Information about fire - and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

Safety Data Sheet according to WHS Regulations

Printing date 07.05.2021 Version number 32 Revision: 13.04.2021

Trade name: Vibra-TITE® VC-3®

(Contd. of page 2)

- Conditions for safe storage, including any incompatibilities

- Storage:
 - Requirements to be met by storerooms and receptacles: No special requirements.
 - Information about storage in one common storage facility: Not required.
 - Further information about storage conditions:

Keep container tightly sealed.

Store in cool, dry conditions in well sealed receptacles.

- Specific end use(s) No further relevant information available.

8 Exposure controls and personal protection

- Additional information about design of technical facilities: No further data; see item 7.
- Control parameters

- Ingredients with limit values that require monitoring at the workplace:

CAS: 78-93-3 methyl ethyl ketone

WES Short-term value: 890 mg/m³, 300 ppm Long-term value: 445 mg/m³, 150 ppm

- Additional information: The lists that were valid during the creation were used as basis.

- Exposure controls

- Personal protective equipment:
 - General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing

Wash hands before breaks and at the end of work.

Avoid contact with the eyes.

Avoid contact with the eyes and skin.

- Respiratory protection:

Not required.

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

Nitrile rubber, NBR

- Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

- **Body protection:** Protective work clothing

9 Physical and Chemical Properties

- Information on basic physical and chemical properties

- General Information
 - Appearance:

- Form: Viscous
- Colour: Red
- Odour: Solvent-like
- Odour threshold: Not determined.

- **pH-value:** Not determined.

- Change in condition

- Melting point/freezing point: Undetermined.
 - Initial boiling point and boiling range: ≥ 79 – ≤ 80.5 °C

- Flash point: ≥ -4 °C

- Flammability (solid, gas): Not applicable.

- Ignition temperature: 410 °C

- **Decomposition temperature:** Not determined.

- Auto-ignition temperature: Product is not selfigniting.

Safety Data Sheet according to WHS Regulations

Printing date 07.05.2021 Version number 32 Revision: 13.04.2021

Trade name: Vibra-TITE® VC-3®

(Contd. of page 4)

- Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
- Explosion limits:	
- Lower:	1.8 Vol %
- Upper:	11.5 Vol %
- Vapour pressure at 20 °C:	≤ 105 hPa
- Density:	Not determined.
Relative density	Not determined.
 Vapour density 	Not determined.
 Evaporation rate 	Not determined.
- Solubility in / Miscibility with	
- water:	Not miscible or difficult to mix.
- Partition coefficient: n-octanol	/water: Not determined.
- Viscosity:	
Dynamic:	Not determined.
- Kinematic at 40 °C:	250 mm ² /s
- Solvent content:	
 Organic solvents: 	60.2 %
- VOC (EC)	60.20 %
- Solids content:	34.3 %
- Other information	No further relevant information available.

10 Stability and Reactivity

- Reactivity No further relevant information available.
- Chemical stability
 - Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- Possibility of hazardous reactions No dangerous reactions known.
- Conditions to avoid No further relevant information available.
- Incompatible materials: No further relevant information available.
- Hazardous decomposition products:

Aldehyde

Hydrocarbons

11 Toxicological Information

- Information on toxicological effects
 - Acute toxicity

- LD/LC50 values relevant for classification:					
CAS: 78	CAS: 78-93-3 methyl ethyl ketone				
Oral	LD50	3,300 mg/kg (rat)			
Dermal	LD50	5,000 mg/kg (rabbit)			

- Primary irritant effect:
 - Skin corrosion/irritation No irritant effect.
 - Serious eye damage/irritation Irritating effect.
- Respiratory or skin sensitisation No sensitising effects known.
- Additional toxicological information:

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological Information

- Toxicity
 - Aquatic toxicity: No further relevant information available.
- Persistence and degradability No further relevant information available.
- Behaviour in environmental systems:
 - Bioaccumulative potential No further relevant information available.
 - Mobility in soil No further relevant information available.

(Contd. of page 4)

Safety Data Sheet according to WHS Regulations

Printing date 07.05.2021 Version number 32 Revision: 13.04.2021

Trade name: Vibra-TITE® VC-3®

- Additional ecological information:

- General notes:

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

- Results of PBT and vPvB assessment
 - PBT: Not applicable.
 - vPvB: Not applicable.
- Other adverse effects No further relevant information available.

13 Disposal considerations

- Waste treatment methods
 - Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.
- Uncleaned packaging:
 - Recommendation: Disposal must be made according to official regulations.

14 Transport information	
- UN-Number - ADG, IMDG, IATA	UN1139
- UN proper shipping name - ADG - IMDG, IATA	UN1139 COATING SOLUTION COATING SOLUTION
- Transport hazard class(es) - ADG, IMDG, IATA	
- Class - Label	3 Flammable liquids. 3
- Packing group - ADG, IMDG, IATA	II
- Environmental hazards: - Marine pollutant:	No
 Special precautions for user Hazard identification number (Kemler code): EMS Number: Stowage Category 	Warning: Flammable liquids. 33 F-E, <u>S-E</u> B
- Transport in bulk according to Annex II of Marpol and the IBC Code	d Not applicable.
- Transport/Additional information:	
- ADG - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
 Transport category Tunnel restriction code 	2 D/E
- IMDG - Limited quantities (LQ) - Excepted quantities (EQ)	5L Code: E2 Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml
- UN "Model Regulation":	UN 1139 COATING SOLUTION, 3, II
	(Contd. on page 6)

Safety Data Sheet according to WHS Regulations

Printing date 07.05.2021 Version number 32 Revision: 13.04.2021

Trade name: Vibra-TITE® VC-3®

(Contd. of page 6)

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Au	stralian Inventory of Industrial Chemicals	
All ingredients a	re listed.	
- Sta	ndard for the Uniform Scheduling of Medicines and Poisons	
CAS: 78-93-3	methyl ethyl ketone	S5
CAS: 108-88-3	toluene	S6
CAS: 111-76-2	2-butoxyethanol	S6

- Directive 2012/18/EU

- Named dangerous substances ANNEX I None of the ingredients is listed.
- Seveso category P5c FLAMMABLE LIQUIDS
- Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Relevant phrases

H225 Highly flammable liquid and vapour.

H319 Causes serious eye irritation.

H336 May cause drowsiness or dizziness.

- Department issuing SDS: ND Industries, Inc. Safety, Health and Environmental Affaires
- **Contact:** Safety, Health and Environmental Affaires
- Classification System:

- Abbreviations and acronyms:

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU) LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Eye Irrit. 2: Serious eye damage/eye irritation – Category 2

STOT SE 3: Specific target organ toxicity (single exposure) - Category 3

Disclaimer

The information set forth is based on information that ND Industries, Incorporated believes to be accurate. No warranty, expressed or implied, is intended. The information is provided solely for your information and consideration and ND Industries Inc. assumes no legal responsibility for use or reliance thereon. In the event of a discrepancy between the information on the non-English document and its English counterpart, the English version shall supersede.

®ND and ND Industries, Inc. are registered trademarks of ND Industries Incorporated, ®Vibra-TITE is a registered trademark of ND Industries, Inc.