



## Megacryl S130 (Part B)

### Engineering Adhesives & Lubricants (Aust) Pty Ltd

Part Number: **Not Available**

Version No: **1.6**

Safety Data Sheet according to Work Health and Safety Regulations (Hazardous Chemicals) 2023 and ADG requirements

Issue Date: **09/01/2025**

Print Date: **09/01/2025**

L.GHS.AUS.EN

#### SECTION 1 Identification of the substance / mixture and of the company / undertaking

##### Product Identifier

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| <b>Product name</b>                  | Megacryl S130 (Part B)                |
| <b>Synonyms</b>                      | Not Available                         |
| <b>Proper shipping name</b>          | ADHESIVES containing flammable liquid |
| <b>Other means of identification</b> | Not Available                         |

##### Relevant identified uses of the substance or mixture and uses advised against

|                                 |                     |
|---------------------------------|---------------------|
| <b>Relevant identified uses</b> | Structural Adhesive |
|---------------------------------|---------------------|

##### Details of the manufacturer or supplier of the safety data sheet

|                                |  |
|--------------------------------|--|
| <b>Registered company name</b> | Engineering Adhesives & Lubricants (Aust) Pty Ltd                |
| <b>Address</b>                 | Unit 3 / 119 Olympic Circuit Southport Queensland 4215 Australia |
| <b>Telephone</b>               | (07) 5531-4242   |
| <b>Fax</b>                     | Not Available  |
| <b>Website</b>                 | <a href="http://www.eal.com.au">www.eal.com.au</a>               |
| <b>Email</b>                   | info@eal.com.au  |

##### Emergency telephone number

|  |                            |
|--|----------------------------|
| <b>Association / Organisation</b>          | Poisons Information Centre |
| <b>Emergency telephone number(s)</b>       | 13 11 26                   |
| <b>Other emergency telephone number(s)</b> | Not Available              |

#### SECTION 2 Hazards identification

##### Classification of the substance or mixture

**HAZARDOUS CHEMICAL. DANGEROUS GOODS. According to the WHS Regulations and the ADG Code.**

|                                      |   |
|--------------------------------------|---|
| <b>Poisons Schedule</b>              | Not Applicable  |
| <b>Classification <sup>[1]</sup></b> | Flammable Liquids Category 2, Skin Corrosion/Irritation Category 2, Sensitisation (Skin) Category 1, Serious Eye Damage/Eye Irritation Category 2A, Specific Target Organ Toxicity - Single Exposure (Respiratory Tract Irritation) Category 3, Specific Target Organ Toxicity - Single Exposure (Narcotic Effects) Category 3, Germ Cell Mutagenicity Category 2, Hazardous to the Aquatic Environment Long-Term Hazard Category 2 |
| <b>Legend:</b>                       | 1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI  |

##### Label elements

**Megacryl S130 (Part B)**

|                            |   |
|----------------------------|---|
| <b>Hazard pictogram(s)</b> |     |
|----------------------------|---|

|                    |               |
|--------------------|---------------|
| <b>Signal word</b> | <b>Danger</b> |
|--------------------|---------------|

**Hazard statement(s)**

|             |  |
|-------------|--|
| <b>H225</b> | Highly flammable liquid and vapour.              |
| <b>H315</b> | Causes skin irritation.                          |
| <b>H317</b> | May cause an allergic skin reaction.             |
| <b>H319</b> | Causes serious eye irritation.                   |
| <b>H335</b> | May cause respiratory irritation.                |
| <b>H336</b> | May cause drowsiness or dizziness.               |
| <b>H341</b> | Suspected of causing genetic defects.            |
| <b>H411</b> | Toxic to aquatic life with long lasting effects. |

**Supplementary statement(s)**

Not Applicable

**Precautionary statement(s) Prevention**

|             |  |
|-------------|--|
| <b>P201</b> | Obtain special instructions before use.  |
| <b>P210</b> | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| <b>P271</b> | Use only outdoors or in a well-ventilated area.  |
| <b>P280</b> | Wear protective gloves, protective clothing, eye protection and face protection.               |
| <b>P240</b> | Ground and bond container and receiving equipment.   |
| <b>P241</b> | Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.              |
| <b>P242</b> | Use non-sparking tools.  |
| <b>P243</b> | Take action to prevent static discharges.  |
| <b>P261</b> | Avoid breathing mist/vapours/spray.  |
| <b>P273</b> | Avoid release to the environment.  |
| <b>P264</b> | Wash all exposed external body areas thoroughly after handling.                                |
| <b>P272</b> | Contaminated work clothing should not be allowed out of the workplace.                         |

**Precautionary statement(s) Response**

|                       |  |
|-----------------------|--|
| <b>P308+P313</b>      | IF exposed or concerned: Get medical advice/ attention.  |
| <b>P370+P378</b>      | In case of fire: Use alcohol resistant foam or normal protein foam to extinguish.  |
| <b>P302+P352</b>      | IF ON SKIN: Wash with plenty of water.   |
| <b>P305+P351+P338</b> | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |
| <b>P312</b>           | Call a POISON CENTER/doctor/physician/first aider/if you feel unwell.  |
| <b>P333+P313</b>      | If skin irritation or rash occurs: Get medical advice/attention.   |
| <b>P337+P313</b>      | If eye irritation persists: Get medical advice/attention.  |
| <b>P362+P364</b>      | Take off contaminated clothing and wash it before reuse.   |
| <b>P391</b>           | Collect spillage.  |
| <b>P303+P361+P353</b> | IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].                         |
| <b>P304+P340</b>      | IF INHALED: Remove person to fresh air and keep comfortable for breathing.   |

**Precautionary statement(s) Storage**

|                  |  |
|------------------|--|
| <b>P403+P235</b> | Store in a well-ventilated place. Keep cool. |
| <b>P405</b>      | Store locked up.                             |

**Precautionary statement(s) Disposal**

|             |  |
|-------------|--|
| <b>P501</b> | Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation. |
|-------------|--|

**Megacryl S130 (Part B)**

## SECTION 3 Composition / information on ingredients

### Substances

See section below for composition of Mixtures

### Mixtures

| CAS No   | %[weight] | Name   |
|--|-----------|--|
| 80-62-6  | 60-80     | <u>methyl methacrylate</u>                               |
| 34562-31-7   | 5-10      | <u>3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine</u> |
| 110-82-7   | <0.05     | <u>cyclohexane</u>                                       |
| 62-53-3  | <0.01     | <u>aniline</u>   |
| <b>Legend:</b> 1. Classification by vendor; 2. Classification drawn from HCIS; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI; 4. Classification drawn from C&L; * EU IOELVs available |           |  |

## SECTION 4 First aid measures

### Description of first aid measures

|                     |  |
|---------------------|--|
| <b>Eye Contact</b>  | <p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"><li>▶ Wash out immediately with fresh running water.</li><li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li><li>▶ Seek medical attention without delay; if pain persists or recurs seek medical attention.</li><li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li></ul>                                     |
| <b>Skin Contact</b> | <p>If skin contact occurs:</p> <ul style="list-style-type: none"><li>▶ Immediately remove all contaminated clothing, including footwear.</li><li>▶ Flush skin and hair with running water (and soap if available).</li><li>▶ Seek medical attention in event of irritation.</li></ul>  |
| <b>Inhalation</b>   | <ul style="list-style-type: none"><li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li><li>▶ Lay patient down. Keep warm and rested.</li><li>▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li><li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li><li>▶ Transport to hospital, or doctor, without delay.</li></ul> |
| <b>Ingestion</b>    | <ul style="list-style-type: none"><li>▶ Immediately give a glass of water.</li><li>▶ First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li></ul>   |

### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

For methyl methacrylate:

Significant effects developing over a work-shift are not detected by symptomatology, blood pressure, respiratory function testing, haemoglobin and white cell count, urinalysis and blood chemistry. Effects may occur in high concentration exposure groups with regard to serum glucose and blood urea, nitrogen, cholesterol, albumin and total bilirubin values. Possible alterations occur in skin and nervous system symptomatology, urinalysis findings and serum triglycerides. Diagnostic signs taken as indicative of methyl methacrylate-induced local neurotoxicity include sensory nerve distal conduction velocities. These deficits appear to result from diffusion of the substance into neurons, lysis of membrane lipids and demyelination.

## SECTION 5 Firefighting measures

### Extinguishing media

### Special hazards arising from the substrate or mixture

|                             |  |
|-----------------------------|--|
| <b>Fire Incompatibility</b> | ▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result |
|-----------------------------|--|

### Advice for firefighters

|                              |  |
|------------------------------|--|
| <b>Fire Fighting</b>         |  |
| <b>Fire/Explosion Hazard</b> | <ul style="list-style-type: none"><li>▶ Liquid and vapour are highly flammable.</li><li>▶ Severe fire hazard when exposed to heat, flame and/or oxidisers.</li><li>▶ Vapour may travel a considerable distance to source of ignition.</li><li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li><li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li></ul> <p>Combustion products include:<br/>carbon dioxide (CO<sub>2</sub>)<br/>nitrogen oxides (NO<sub>x</sub>)<br/>other pyrolysis products typical of burning organic material.</p> |

**Megacryl S130 (Part B)**

|                |                                |
|----------------|--------------------------------|
|                | May emit clouds of acrid smoke |
| <b>HAZCHEM</b> | •3YE                           |

## SECTION 6 Accidental release measures

### Personal precautions, protective equipment and emergency procedures

See section 8

### Environmental precautions

See section 12

### Methods and material for containment and cleaning up

|                     |   |
|---------------------|---|
| <b>Minor Spills</b> | <ul style="list-style-type: none"><li>▶ Remove all ignition sources.</li><li>▶ Clean up all spills immediately.</li><li>▶ Avoid breathing vapours and contact with skin and eyes.</li><li>▶ Control personal contact with the substance, by using protective equipment.</li><li>▶ Contain and absorb small quantities with vermiculite or other absorbent material.</li><li>▶ Wipe up.</li><li>▶ Collect residues in a flammable waste container.</li></ul>   |
| <b>Major Spills</b> | <ul style="list-style-type: none"><li>▶ Clear area of personnel and move upwind.</li><li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li><li>▶ Wear breathing apparatus plus protective gloves.</li><li>▶ Prevent, by any means available, spillage from entering drains or water course.</li><li>▶ Stop leak if safe to do so.</li><li>▶ Contain spill with sand, earth or vermiculite.</li><li>▶ Collect recoverable product into labelled containers for recycling.</li><li>▶ Neutralise/decontaminate residue (see Section 13 for specific agent).</li><li>▶ Collect solid residues and seal in labelled drums for disposal.</li><li>▶ Wash area and prevent runoff into drains.</li><li>▶ After clean up operations, decontaminate and launder all protective clothing and equipment before storing and re-using.</li><li>▶ If contamination of drains or waterways occurs, advise emergency services.</li></ul> |

Personal Protective Equipment advice is contained in Section 8 of the SDS.

## SECTION 7 Handling and storage

### Precautions for safe handling

|                          |  |
|--------------------------|--|
| <b>Safe handling</b>     | <ul style="list-style-type: none"><li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li><li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li><li>▶ Avoid all personal contact, including inhalation.</li><li>▶ Wear protective clothing when risk of exposure occurs.</li><li>▶ Use in a well-ventilated area.</li><li>▶ Prevent concentration in hollows and sumps.</li><li>▶ <b>DO NOT enter confined spaces until atmosphere has been checked.</b></li><li>▶ Avoid smoking, naked lights, heat or ignition sources.</li><li>▶ When handling, <b>DO NOT eat, drink or smoke.</b></li><li>▶ Vapour may ignite on pumping or pouring due to static electricity.</li><li>▶ <b>DO NOT use plastic buckets.</b></li><li>▶ Earth and secure metal containers when dispensing or pouring product.</li><li>▶ Use spark-free tools when handling.</li><li>▶ Avoid contact with incompatible materials.</li><li>▶ Keep containers securely sealed.</li><li>▶ Avoid physical damage to containers.</li><li>▶ Always wash hands with soap and water after handling.</li><li>▶ Work clothes should be laundered separately.</li><li>▶ Use good occupational work practice.</li><li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li><li>▶ Atmosphere should be regularly checked against established exposure standards to ensure safe working conditions.</li><li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li></ul> |
| <b>Other information</b> | <ul style="list-style-type: none"><li>▶ Store below 38 deg. C.</li><li>▶ Store in original containers in approved flame-proof area.</li><li>▶ No smoking, naked lights, heat or ignition sources.</li><li>▶ <b>DO NOT store in pits, depression, basement or areas where vapours may be trapped.</b></li><li>▶ Keep containers securely sealed.</li><li>▶ Store away from incompatible materials in a cool, dry well ventilated area.</li><li>▶ Protect containers against physical damage and check regularly for leaks.</li><li>▶ Observe manufacturer's storage and handling recommendations contained within this SDS.</li><li>▶ Tank storage: Tanks must be specifically designed for use with this product. Bulk storage tanks should be diked (bunded). Locate tanks away from heat and other sources of ignition. Cleaning, inspection and maintenance of storage tanks is a specialist operation, which requires the implementation of strict procedures and precautions.</li></ul>   |

- ▶ Keep in a cool place. Electrostatic charges will be generated during pumping. Electrostatic discharge may cause fire. Ensure electrical continuity by bonding and grounding (earthing) all equipment to reduce the risk. The vapours in the head space of the storage vessel may lie in the flammable/explosive range and hence may be flammable.
- ▶ For containers, or container linings use mild steel, stainless steel. Examples of suitable materials are: high density polyethylene (HDPE), polypropylene (PP), and Viton (FMK), which have been specifically tested for compatibility with this product.
- ▶ For container linings, use amine-adduct cured epoxy paint.
- ▶ For seals and gaskets use: graphite, PTFE, Viton A, Viton B.
- ▶ Unsuitable material: Some synthetic materials may be unsuitable for containers or container linings depending on the material specification and intended use. Examples of materials to avoid are: natural rubber (NR), nitrile rubber (NBR), ethylene propylene rubber (EPDM), polymethyl methacrylate (PMMA), polystyrene, polyvinyl chloride (PVC), polyisobutylene. However, some may be suitable for glove materials.
- ▶ Do not cut, drill, grind, weld or perform similar operations on or near containers. Containers, even those that have been emptied, can contain explosive vapours.

Conditions for safe storage, including any incompatibilities

|                         |  |
|-------------------------|--|
| Suitable container      | <p>For acrylates or methacrylates:</p> <p>Storage tanks and pipes should be made of stainless steel or aluminium.</p> <p>Although they do not corrode carbon steel, there is a risk of contamination if corrosion does occur.</p> <ul style="list-style-type: none"><li>▶ Packing as supplied by manufacturer.</li><li>▶ Plastic containers may only be used if approved for flammable liquid.</li><li>▶ Check that containers are clearly labelled and free from leaks.</li><li>▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li><li>▶ For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li><li>▶ For manufactured product having a viscosity of at least 250 cSt. (23 deg. C)</li><li>▶ Manufactured product that requires stirring before use and having a viscosity of at least 20 cSt (25 deg. C): (i) Removable head packaging; (ii) Cans with friction closures and (iii) low pressure tubes and cartridges may be used.</li><li>▶ Where combination packages are used, and the inner packages are of glass, there must be sufficient inert cushioning material in contact with inner and outer packages</li><li>▶ In addition, where inner packagings are glass and contain liquids of packing group I there must be sufficient inert absorbent to absorb any spillage, unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.</li></ul> |
| Storage incompatibility | <p>Methyl acrylate:</p> <ul style="list-style-type: none"><li>▶ may polymerise explosively when heated above 21 C, or in light, or when when inhibitor concentrations fall to low levels</li><li>▶ storage containers may explode at elevated temperatures</li><li>▶ reacts violently with strong oxidisers</li><li>▶ is incompatible with strong acids, alkalis, aliphatic amines, alkanolamines, polyvinyl chloride, mercaptans, nitro- compounds, perborates, azides, ethers, ketones, aldehydes, nitrates, nitrites, reducing agents, acid anhydrides, acid chlorides, concentrated mineral acids, metal salts, strong bases,</li><li>▶ is usually stored below 10 deg C</li><li>▶ vapour may block vents and confined spaces after forming solid polymers</li></ul> <p>NOTE: Contact with alkali solutions will remove inhibitor and render material unstable on storage.</p> <p>Avoid oxygen content of less than 5%</p> <ul style="list-style-type: none"><li>▶ Stable under controlled storage conditions provided material contains adequate stabiliser / polymerisation inhibitor.</li><li>▶ Bulk storages may have special storage requirements</li><li>▶ WARNING: Gradual decomposition in strong, sealed containers may lead to a large pressure build-up and subsequent explosion. Rapid and violent polymerisation possible at temperatures above 32 deg c.</li><li>▶ Avoid reaction with oxidising agents</li></ul>  |



X — Must not be stored together

0 — May be stored together with specific preventions

+

Note: Depending on other risk factors, compatibility assessment based on the table above may not be relevant to storage situations, particularly where large volumes of dangerous goods are stored and handled. Reference should be made to the Safety Data Sheets for each substance or article and risks assessed accordingly.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

| Source                       | Ingredient          | Material name       | TWA                | STEL                | Peak          | Notes         |
|------------------------------|---------------------|---------------------|--------------------|---------------------|---------------|---------------|
| Australia Exposure Standards | methyl methacrylate | Methyl methacrylate | 50 ppm / 208 mg/m3 | 416 mg/m3 / 100 ppm | Not Available | Not Available |

Megacryl S130 (Part B)

| Source                       | Ingredient  | Material name        | TWA                 | STEL                 | Peak          | Notes         |
|------------------------------|-------------|----------------------|---------------------|----------------------|---------------|---------------|
| Australia Exposure Standards | cyclohexane | Cyclohexane          | 100 ppm / 350 mg/m3 | 1050 mg/m3 / 300 ppm | Not Available | Not Available |
| Australia Exposure Standards | aniline     | Aniline & homologues | 2 ppm / 7.6 mg/m3   | Not Available        | Not Available | Not Available |

| Ingredient  | Original IDLH | Revised IDLH  |
|---|---------------|---------------|
| methyl methacrylate                               | 1,000 ppm     | Not Available |
| 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine | Not Available | Not Available |
| cyclohexane                                       | Not Available | Not Available |
| aniline   | 100 ppm       | Not Available |

Occupational Exposure Banding

| Ingredient  | Occupational Exposure Band Rating  | Occupational Exposure Band Limit |
|---|--|----------------------------------|
| 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine | D  | > 0.1 to ≤ 1 ppm                 |
| Notes:  | Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health. |                                  |

MATERIAL DATA

IFRA Prohibited Fragrance Substance

The International Fragrance Association (IFRA) Standards form the basis for the globally accepted and recognized risk management system for the safe use of fragrance ingredients and are part of the IFRA Code of Practice. This is the self-regulating system of the industry, based on risk assessments carried out by an independent Expert Panel

For aniline:

Odour Threshold Value: 0.58-10 ppm (detection)

Threshold odour concentration, 50% recognition is >0.1 ppm, identification at 1 ppm.

NOTE: Detector tubes for aniline, measuring in excess of 0.5 ppm are commercially available.

Increased levels of methaemoglobin are detected in the blood of animals exposed at 5 ppm and following skin exposure by humans. The TLV-TWA is thought to provide protection against the significant risk of systemic effects.

Odour Safety Factor(OSF)

OSF=0.91 (ANILINE)

Exposed individuals are **NOT** reasonably expected to be warned, by smell, that the Exposure Standard is being exceeded.

Odour Safety Factor (OSF) is determined to fall into either Class C, D or E.

The Odour Safety Factor (OSF) is defined as:

OSF= Exposure Standard (TWA) ppm/ Odour Threshold Value (OTV) ppm

Classification into classes follows:

| Class | OSF    | Description  |
|-------|--------|--|
| A     | 550    | Over 90% of exposed individuals are aware by smell that the Exposure Standard (TLV-TWA for example) is being reached, even when distracted by working activities |
| B     | 26-550 | As "A" for 50-90% of persons being distracted  |
| C     | 1-26   | As "A" for less than 50% of persons being distracted   |
| D     | 0.18-1 | 10-50% of persons aware of being tested perceive by smell that the Exposure Standard is being reached  |
| E     | <0.18  | As "D" for less than 10% of persons aware of being tested  |

For cyclohexane:

Odour Threshold Value: 784 ppm (detection)

NOTE: Detector tubes for cyclohexane, measuring in excess of 100 ppm are commercially available.

The recommended TLV-TWA represents the borderline of irritation but takes into account the practical difficulties of achieving lower values in the workplace. Whether serious or long-lasting consequences result from exposure at 300 ppm or whether humans become narcosed or fatigued remains to be established. The present value is thought to be a satisfactory bench-mark until further studies are made.

Odour Safety Factor(OSF)

OSF=4 (CYCLOHEXANE)

Odour Threshold Value (methyl methacrylate): 0.049 ppm (detection), 0.34 ppm (recognition)

NOTE: Detector tubes measuring in excess of 50 ppm, are available.

Concentrations as low as 125 ppm methyl methacrylate have produced irritation of the mucous membranes of exposed workers. The recommended TLV-TWA is thought to be sufficiently low to protect against discomfort from irritation and acute systemic intoxication.

Exposure controls

## Megacryl S130 (Part B)

### Appropriate engineering controls

Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.

The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use. Employers may need to use multiple types of controls to prevent employee overexposure.

For flammable liquids and flammable gases, local exhaust ventilation or a process enclosure ventilation system may be required. Ventilation equipment should be explosion-resistant.

Air contaminants generated in the workplace possess varying "escape" velocities which, in turn, determine the "capture velocities" of fresh circulating air required to effectively remove the contaminant.

| Type of Contaminant:  | Air Speed:                   |
|---|------------------------------|
| solvent, vapours, degreasing etc., evaporating from tank (in still air).  | 0.25-0.5 m/s (50-100 f/min.) |
| aerosols, fumes from pouring operations, intermittent container filling, low speed conveyer transfers, welding, spray drift, plating acid fumes, pickling (released at low velocity into zone of active generation) | 0.5-1 m/s (100-200 f/min.)   |
| direct spray, spray painting in shallow booths, drum filling, conveyer loading, crusher dusts, gas discharge (active generation into zone of rapid air motion)  | 1-2.5 m/s (200-500 f/min.)   |

Within each range the appropriate value depends on:

| Lower end of the range                                     | Upper end of the range           |
|--|----------------------------------|
| 1: Room air currents minimal or favourable to capture      | 1: Disturbing room air currents  |
| 2: Contaminants of low toxicity or of nuisance value only. | 2: Contaminants of high toxicity |
| 3: Intermittent, low production.                           | 3: High production, heavy use    |
| 4: Large hood or large air mass in motion                  | 4: Small hood-local control only |

Simple theory shows that air velocity falls rapidly with distance away from the opening of a simple extraction pipe. Velocity generally decreases with the square of distance from the extraction point (in simple cases). Therefore the air speed at the extraction point should be adjusted, accordingly, after reference to distance from the contaminating source. The air velocity at the extraction fan, for example, should be a minimum of 1-2 m/s (200-400 f/min.) for extraction of solvents generated in a tank 2 meters distant from the extraction point. Other mechanical considerations, producing performance deficits within the extraction apparatus, make it essential that theoretical air velocities are multiplied by factors of 10 or more when extraction systems are installed or used.

- Adequate ventilation is typically taken to be that which limits the average concentration to no more than 25% of the LEL within the building, room or enclosure containing the dangerous substance.
- Ventilation for plant and machinery is normally considered adequate if it limits the average concentration of any dangerous substance that might potentially be present to no more than 25% of the LEL. However, an increase up to a maximum 50% LEL can be acceptable where additional safeguards are provided to prevent the formation of a hazardous explosive atmosphere. For example, gas detectors linked to emergency shutdown of the process might be used together with maintaining or increasing the exhaust ventilation on solvent evaporating ovens and gas turbine enclosures.
- Temporary exhaust ventilation systems may be provided for non-routine higher-risk activities, such as cleaning, repair or maintenance in tanks or other confined spaces or in an emergency after a release. The work procedures for such activities should be carefully considered. The atmosphere should be continuously monitored to ensure that ventilation is adequate and the area remains safe. Where workers will enter the space, the ventilation should ensure that the concentration of the dangerous substance does not exceed 10% of the LEL (irrespective of the provision of suitable breathing apparatus)

### Individual protection measures, such as personal protective equipment



### Eye and face protection

- ▶ Safety glasses with side shields.
- ▶ Chemical goggles. [AS/NZS 1337.1, EN166 or national equivalent]
- ▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available. In the event of chemical exposure, begin eye irrigation immediately and remove contact lens as soon as practicable. Lens should be removed at the first signs of eye redness or irritation - lens should be removed in a clean environment only after workers have washed hands thoroughly. [CDC NIOSH Current Intelligence Bulletin 59].

### Skin protection

See Hand protection below

### Hands/feet protection

- ▶ Wear chemical protective gloves, e.g. PVC.
- ▶ Wear safety footwear or safety gumboots, e.g. Rubber

#### NOTE:

- ▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.

## Megacryl S130 (Part B)

|                         |   |
|-------------------------|---|
|                         | <p>▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</p> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</p> <p>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</p> <p>Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> <p>Suitability and durability of glove type is dependent on usage. Important factors in the selection of gloves include:</p> <ul style="list-style-type: none"> <li>· frequency and duration of contact,</li> <li>· chemical resistance of glove material,</li> <li>· glove thickness and</li> <li>· dexterity</li> </ul> <p>Select gloves tested to a relevant standard (e.g. Europe EN 374, US F739, AS/NZS 2161.1 or national equivalent).</p> <ul style="list-style-type: none"> <li>· When prolonged or frequently repeated contact may occur, a glove with a protection class of 5 or higher (breakthrough time greater than 240 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· When only brief contact is expected, a glove with a protection class of 3 or higher (breakthrough time greater than 60 minutes according to EN 374, AS/NZS 2161.10.1 or national equivalent) is recommended.</li> <li>· Some glove polymer types are less affected by movement and this should be taken into account when considering gloves for long-term use.</li> <li>· Contaminated gloves should be replaced.</li> </ul> <p>As defined in ASTM F-739-96 in any application, gloves are rated as:</p> <ul style="list-style-type: none"> <li>· Excellent when breakthrough time &gt; 480 min</li> <li>· Good when breakthrough time &gt; 20 min</li> <li>· Fair when breakthrough time &lt; 20 min</li> <li>· Poor when glove material degrades</li> </ul> <p>For general applications, gloves with a thickness typically greater than 0.35 mm, are recommended.</p> <p>It should be emphasised that glove thickness is not necessarily a good predictor of glove resistance to a specific chemical, as the permeation efficiency of the glove will be dependent on the exact composition of the glove material. Therefore, glove selection should also be based on consideration of the task requirements and knowledge of breakthrough times.</p> <p>Glove thickness may also vary depending on the glove manufacturer, the glove type and the glove model. Therefore, the manufacturers technical data should always be taken into account to ensure selection of the most appropriate glove for the task.</p> <p>Note: Depending on the activity being conducted, gloves of varying thickness may be required for specific tasks. For example:</p> <ul style="list-style-type: none"> <li>· Thinner gloves (down to 0.1 mm or less) may be required where a high degree of manual dexterity is needed. However, these gloves are only likely to give short duration protection and would normally be just for single use applications, then disposed of.</li> <li>· Thicker gloves (up to 3 mm or more) may be required where there is a mechanical (as well as a chemical) risk i.e. where there is abrasion or puncture potential</li> </ul> <p>Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.</p> |
| <b>Body protection</b>  | See Other protection below  |
| <b>Other protection</b> | <ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> <li>▶ Ensure there is ready access to a safety shower.</li> <li>▶ Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</li> <li>▶ For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).</li> <li>▶ Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds. Electrical resistance must range between 0 to 500,000 ohms. Conductive shoes should be stored in lockers close to the room in which they are worn. Personnel who have been issued conductive footwear should not wear them from their place of work to their homes and return.</li> </ul>   |

### Ansell Glove Selection

| Glove — In order of recommendation |
|------------------------------------|
| AlphaTec® 38-612                   |
| AlphaTec® 15-554                   |
| AlphaTec® 53-001                   |
| AlphaTec® 58-005                   |
| AlphaTec® Solvex® 37-175           |
| BioClean™ Emerald BENS             |
| BioClean™ Extra BLAS               |
| BioClean™ Fusion (Sterile) S-BFAP  |
| BioClean™ N-Plus BNPS              |
| BioClean™ Ultimate BUPs            |

The suggested gloves for use should be confirmed with the glove supplier.

### Respiratory protection

Type KAX Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

| Required Minimum Protection Factor | Half-Face Respirator | Full-Face Respirator | Powered Air Respirator |
|------------------------------------|----------------------|----------------------|------------------------|
| up to 10 x ES                      | KAX-AUS              | -                    | KAX-PAPR-AUS / Class 1 |
| up to 50 x ES                      | -                    | KAX-AUS / Class 1    | -                      |
| up to 100 x ES                     | -                    | KAX-2                | KAX-PAPR-2 ^           |

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur



## Megacryl S130 (Part B)

dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- ▶ Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- ▶ The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- ▶ Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

## SECTION 9 Physical and chemical properties

### Information on basic physical and chemical properties

|   |                   |  |               |
|---|-------------------|--|---------------|
| <b>Appearance</b>                                     | Yellow            |  |               |
| <b>Physical state</b>                                 | Liquid            | <b>Relative density (Water = 1)</b>                        | Not Available |
| <b>Odour</b>  | Not Available     | <b>Partition coefficient n-octanol / water</b>             | Not Available |
| <b>Odour threshold</b>                                | Not Available     | <b>Auto-ignition temperature (°C)</b>                      | Not Available |
| <b>pH (as supplied)</b>                               | Not Available     | <b>Decomposition temperature (°C)</b>                      | Not Available |
| <b>Melting point / freezing point (°C)</b>            | Not Available     | <b>Viscosity (cSt)</b>                                     | Not Available |
| <b>Initial boiling point and boiling range (°C)</b>   | Not Available     | <b>Molecular weight (g/mol)</b>                            | Not Available |
| <b>Flash point (°C)</b>                               | 12                | <b>Taste</b>   | Not Available |
| <b>Evaporation rate</b>                               | Not Available     | <b>Explosive properties</b>                                | Not Available |
| <b>Flammability</b>                                   | HIGHLY FLAMMABLE. | <b>Oxidising properties</b>                                | Not Available |
| <b>Upper Explosive Limit (%)</b>                      | Not Available     | <b>Surface Tension (dyn/cm or mN/m)</b>                    | Not Available |
| <b>Lower Explosive Limit (%)</b>                      | Not Available     | <b>Volatile Component (%vol)</b>                           | Not Available |
| <b>Vapour pressure (kPa)</b>                          | Not Available     | <b>Gas group</b>   | Not Available |
| <b>Solubility in water</b>                            | Not Applicable    | <b>pH as a solution (1%)</b>                               | Not Available |
| <b>Vapour density (Air = 1)</b>                       | Not Available     | <b>VOC g/L</b>   | Not Available |
| <b>Heat of Combustion (kJ/g)</b>                      | Not Available     | <b>Ignition Distance (cm)</b>                              | Not Available |
| <b>Flame Height (cm)</b>                              | Not Available     | <b>Flame Duration (s)</b>                                  | Not Available |
| <b>Enclosed Space Ignition Time Equivalent (s/m3)</b> | Not Available     | <b>Enclosed Space Ignition Deflagration Density (g/m3)</b> | Not Available |

## SECTION 10 Stability and reactivity

|   |   |
|---|---|
| <b>Reactivity</b>                         | See section 7   |
| <b>Chemical stability</b>                 | <ul style="list-style-type: none"> <li>▶ Stable under controlled storage conditions provided material contains adequate stabiliser / polymerisation inhibitor.</li> <li>▶ Bulk storages may have special storage requirements</li> <li>▶ WARNING: Gradual decomposition in strong, sealed containers may lead to a large pressure build-up and subsequent explosion. Rapid and violent polymerisation possible at temperatures above 32 deg c.</li> </ul> |
| <b>Possibility of hazardous reactions</b> | See section 7   |
| <b>Conditions to avoid</b>                | See section 7   |
| <b>Incompatible materials</b>             | See section 7   |
| <b>Hazardous decomposition products</b>   | See section 5   |

## SECTION 11 Toxicological information

**Megacryl S130 (Part B)**

**Information on toxicological effects**

|                     |  |
|---------------------|--|
| <b>Inhaled</b>      | <p>Evidence shows, or practical experience predicts, that the material produces irritation of the respiratory system, in a substantial number of individuals, following inhalation. In contrast to most organs, the lung is able to respond to a chemical insult by first removing or neutralising the irritant and then repairing the damage. The repair process, which initially evolved to protect mammalian lungs from foreign matter and antigens, may however, produce further lung damage resulting in the impairment of gas exchange, the primary function of the lungs. Respiratory tract irritation often results in an inflammatory response involving the recruitment and activation of many cell types, mainly derived from the vascular system.</p> <p>Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by narcosis, reduced alertness, loss of reflexes, lack of coordination and vertigo.</p> <p>Workers in plants manufacturing methyl methacrylate have complained of headaches, pains in the extremities, fatigue, sleep disturbance, irritability and loss of memory. A Russian report associated disturbances in the level of insulin, prolactin and circulating somatotrophic hormone in women to occupational exposure to methyl methacrylate.</p> <p>Inhalation of 47 ppm in dogs produces hypotension, signs of central nervous system (CNS) depression, hepatic and renal degeneration and death in respiratory arrest</p> <p>Inhalation of aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful.</p> <p>If exposure to highly concentrated vapour atmosphere is prolonged this may lead to narcosis, unconsciousness, even coma and unless resuscitated - death.</p>  |
| <b>Ingestion</b>    | <p>The material is not thought to produce adverse health effects following ingestion (as classified by EC Directives using animal models). Nevertheless, adverse systemic effects have been produced following exposure of animals by at least one other route and good hygiene practice requires that exposure be kept to a minimum.</p> <p>At sufficiently high doses the material may be hepatotoxic (i.e. poisonous to the liver). Signs may include nausea, stomach pains, low fever, loss of appetite, dark urine, clay-coloured stools, jaundice (yellowing of the skin or eyes)</p> <p>Oral doses of 5 ml/kg methyl methacrylate in dogs produce hypotension, signs of central nervous system (CNS) depression, hepatic and renal degeneration and death in respiratory arrest</p> <p>Central nervous system (CNS) depression may include nonspecific discomfort, symptoms of giddiness, headache, dizziness, nausea, anaesthetic effects, slowed reaction time, slurred speech and may progress to unconsciousness. Serious poisonings may result in respiratory depression and may be fatal.</p> <p>Accidental ingestion of the material may be damaging to the health of the individual.</p>  |
| <b>Skin Contact</b> | <p>Evidence exists, or practical experience predicts, that the material either produces inflammation of the skin in a substantial number of individuals following direct contact, and/or produces significant inflammation when applied to the healthy intact skin of animals, for up to four hours, such inflammation being present twenty-four hours or more after the end of the exposure period.</p> <p>Skin irritation may also be present after prolonged or repeated exposure; this may result in a form of contact dermatitis (nonallergic). The dermatitis is often characterised by skin redness (erythema) and swelling (oedema) which may progress to blistering (vesiculation), scaling and thickening of the epidermis. At the microscopic level there may be intercellular oedema of the spongy layer of the skin (spongiosis) and intracellular oedema of the epidermis.</p> <p>The material may accentuate any pre-existing dermatitis condition</p> <p>Reports of dental technicians, surgeons and manufacturing employees with direct skin contact with methyl methacrylate document paresthesias of the digits and mild local axonal degeneration.</p> <p>Open cuts, abraded or irritated skin should not be exposed to this material</p> <p>Entry into the blood-stream through, for example, cuts, abrasions, puncture wounds or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.</p>   |
| <b>Eye</b>          | <p>Evidence exists, or practical experience predicts, that the material may cause eye irritation in a substantial number of individuals and/or may produce significant ocular lesions which are present twenty-four hours or more after instillation into the eye(s) of experimental animals.</p> <p>Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.</p>   |
| <b>Chronic</b>      | <p>Long-term exposure to respiratory irritants may result in disease of the airways involving difficult breathing and related systemic problems.</p> <p>Strong evidence exists that the substance may cause irreversible but non-lethal mutagenic effects following a single exposure.</p> <p>Practical evidence shows that inhalation of the material is capable of inducing a sensitisation reaction in a substantial number of individuals at a greater frequency than would be expected from the response of a normal population.</p> <p>Pulmonary sensitisation, resulting in hyperactive airway dysfunction and pulmonary allergy may be accompanied by fatigue, malaise and aching. Significant symptoms of exposure may persist for extended periods, even after exposure ceases. Symptoms can be activated by a variety of nonspecific environmental stimuli such as automobile exhaust, perfumes and passive smoking.</p> <p>Practical experience shows that skin contact with the material is capable either of inducing a sensitisation reaction in a substantial number of individuals, and/or of producing a positive response in experimental animals.</p> <p>Substances that can cause occupational asthma (also known as asthmagens and respiratory sensitisers) can induce a state of specific airway hyper-responsiveness via an immunological, irritant or other mechanism. Once the airways have become hyper-responsive, further exposure to the substance, sometimes even to tiny quantities, may cause respiratory symptoms. These symptoms can range in severity from a runny nose to asthma. Not all workers who are exposed to a sensitizer will become hyper-responsive and it is impossible to identify in advance who are likely to become hyper-responsive.</p> <p>Substances that can cause occupational asthma should be distinguished from substances which may trigger the symptoms of asthma in people with pre-existing air-way hyper-responsiveness. The latter substances are not classified as asthmagens or respiratory sensitisers</p> <p>Wherever it is reasonably practicable, exposure to substances that can cause occupational asthma should be prevented. Where this is not possible the primary aim is to apply adequate standards of control to prevent workers from becoming hyper-responsive.</p> <p>Activities giving rise to short-term peak concentrations should receive particular attention when risk management is being considered. Health surveillance is appropriate for all employees exposed or liable to be exposed to a substance which may cause occupational asthma and there should be appropriate consultation with an occupational health professional over the degree of risk and level of surveillance.</p> <p>Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed.</p> <p>Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe</p> |

Megacryl S130 (Part B)

lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests.

Limited evidence suggests that repeated or long-term occupational exposure may produce cumulative health effects involving organs or biochemical systems.

Prolonged and repeated exposures can cause liver and kidney damage. Hypotension induced by methyl methacrylate in surgical bone cement has been followed by cardiac arrest with at least one fatality in a patient undergoing surgery reported.

An increased mortality from colon and rectal cancer in white male employees exposed for at least 10-months to acrylate monomer (including methyl methacrylate) has been reported in one cohort but not in others where acrylate exposures were controlled.

Incorporation of up to 2000 ppm methyl methacrylate in drinking water of rats for up to two-years did not induce any treatment-related pathology although subcutaneous and intraperitoneal implants of freshly polymerised material for up to 39 months produced local fibrosarcoma.

Inhalation of methyl methacrylate by rats and mice of both sexes produced inflammation of the nasal cavity and degeneration of the olfactory sensory epithelium and epithelial hyperplasia of the nasal cavity in mice (exposure occurred over two years)

On the basis, primarily, of animal experiments, concern has been expressed that the material may produce carcinogenic or mutagenic effects; in respect of the available information, however, there presently exists inadequate data for making a satisfactory assessment.

Inhalation of epoxy resin amine hardener vapours (including polyamines and amine adducts) may produce bronchospasm and coughing episodes lasting days after cessation of the exposure. Even faint traces of these vapours may trigger an intense reaction in individuals showing "amine asthma". The literature records several instances of systemic intoxications following the use of amines in epoxy resin systems.

Excessive exposure to the vapours of epoxy amine curing agents may cause both respiratory irritation and central nervous system depression. Signs and symptoms of central nervous system depression, in order of increasing exposure, are headache, dizziness, drowsiness, and incoordination. In short, a single prolonged (measured in hours) or excessive inhalation exposure may cause serious adverse effects, including death.

|   |   |  |
|---|---|--|
| Megacryl S130 (Part B)                            | TOXICITY  | IRRITATION   |
|   | Not Available                                       | Not Available  |
| methyl methacrylate                               | TOXICITY  | IRRITATION   |
|   | Dermal (rabbit) LD50: >5000 mg/kg <sup>[2]</sup>    | Eye (Rodent - rabbit): 150mg                                     |
|   | Inhalation (Rat) LC50: 29.8 mg/l4h <sup>[1]</sup>   | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>  |
|   | Oral (Rat) LD50: 7872 mg/kg <sup>[2]</sup>          | Skin (Human - woman): 2%/48H                                     |
|   |   | Skin (Rodent - rabbit): 10gm                                     |
|   |   | Skin: adverse effect observed (irritating) <sup>[1]</sup>        |
|   | TOXICITY  | IRRITATION   |
|   | Dermal (rabbit) LD50: >1000 mg/kg <sup>[1]</sup>    | Eye: adverse effect observed (irritating) <sup>[1]</sup>         |
| 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine | Oral (Rat) LD50: >500 mg/kg <sup>[1]</sup>          | Skin: adverse effect observed (irritating) <sup>[1]</sup>        |
|   |   |  |
| cyclohexane                                       | TOXICITY  | IRRITATION   |
|   | Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>    | Eye (Rodent - rabbit): 0.1mL                                     |
|   | Inhalation (Rat) LC50: >5540 ppm4h <sup>[1]</sup>   | Eye (Rodent - rabbit): 0.1mL - Severe                            |
|   | Oral (Rat) LD50: 12705 mg/kg <sup>[2]</sup>         | Eye: no adverse effect observed (not irritating) <sup>[1]</sup>  |
|   |   | Skin (Rodent - rabbit): 1548mg/2D (intermittent)                 |
|   |   | Skin: adverse effect observed (irritating) <sup>[1]</sup>        |
| aniline   |   | Skin: no adverse effect observed (not irritating) <sup>[1]</sup> |
|   | TOXICITY  | IRRITATION   |
|   | dermal (rat) LD50: 1400 mg/kg <sup>[2]</sup>        | Eye (Rodent - rabbit): 0.1mL                                     |
|   | Inhalation (Rat) LC50: >0.525 mg/l4h <sup>[1]</sup> | Eye (Rodent - rabbit): 20mg/24H - Moderate                       |
|   | Oral (Rat) LD50: 250 mg/kg <sup>[2]</sup>           | Skin (Rodent - rabbit): 20mg/24H - Moderate                      |
|   |   |  |

Legend:

1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. Value obtained from manufacturer's SDS.  
Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances

|                        |  |
|------------------------|--|
| Megacryl S130 (Part B) | Allergic reactions which develop in the respiratory passages as bronchial asthma or rhinoconjunctivitis, are mostly the result of reactions of the allergen with specific antibodies of the IgE class and belong in their reaction rates to the manifestation of the immediate type. In addition to the allergen-specific potential for causing respiratory sensitisation, the amount of the allergen, the exposure period and the genetically determined disposition of the exposed person are likely to be decisive. Factors which increase the sensitivity of the mucosa may play a role in predisposing a person to allergy. They may be genetically determined or |
|------------------------|--|

**Megacryl S130 (Part B)**

|  |   |
|--|---|
|  | <p>acquired, for example, during infections or exposure to irritant substances. Immunologically the low molecular weight substances become complete allergens in the organism either by binding to peptides or proteins (haptens) or after metabolism (prohaptens). Particular attention is drawn to so-called atopic diathesis which is characterised by an increased susceptibility to allergic rhinitis, allergic bronchial asthma and atopic eczema (neurodermatitis) which is associated with increased IgE synthesis. Exogenous allergic alveolitis is induced essentially by allergen specific immune-complexes of the IgG type; cell-mediated reactions (T lymphocytes) may be involved. Such allergy is of the delayed type with onset up to four hours following exposure.</p>  |
| <b>METHYL METHACRYLATE</b>                               | <p>Inhalation (human) TCLo: 60 mg/m<sup>3</sup>(15 ppm) [* Manuf. Rohm &amp; Haas]</p> <p>Where no "official" classification for acrylates and methacrylates exists, there has been cautious attempts to create classifications in the absence of contrary evidence. For example</p> <p>Monalkyl or monoarylesters of acrylic acids should be classified as R36/37/38 and R51/53</p> <p>Monoalkyl or monoaryl esters of methacrylic acid should be classified as R36/37/38</p> <p>Based on the available oncogenicity data and without a better understanding of the carcinogenic mechanism the Health and Environmental Review Division (HERD), Office of Toxic Substances (OTS), of the US EPA previously concluded that all chemicals that contain the acrylate or methacrylate moiety (CH<sub>2</sub>=CHCOO or CH<sub>2</sub>=C(CH<sub>3</sub>)COO) should be considered to be a carcinogenic hazard unless shown otherwise by adequate testing.</p> <p>This position has now been revised and acrylates and methacrylates are no longer <i>de facto</i> carcinogens.</p>   |
| <b>3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE</b> | <p>product: &gt;95% * National Starch and Chemical Company NJ, USA</p>  |
| <b>CYCLOHEXANE</b>                                       | <p>Bacteria mutagen</p>   |
| <b>ANILINE</b>   | <p>NOTE: Impure technical grade aniline may also contain toluidines and xylidines which can give increased toxic hazard. Long continued employment in the manufacture of aniline dyes has been associated with the development of papillomatous growths of the bladder, some of which became malignant. Aniline itself has not been proven to be a carcinogen, but the intermediates benzidine and naphthylamines have been incriminated</p> <p>The material may produce severe irritation to the eye causing pronounced inflammation. Repeated or prolonged exposure to irritants may produce conjunctivitis.</p> <p>The material may cause skin irritation after prolonged or repeated exposure and may produce a contact dermatitis (nonallergic). This form of dermatitis is often characterised by skin redness (erythema) and swelling the epidermis. Histologically there may be intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the epidermis.</p> <p><b>NOTE:</b> The substance is classified under EC Directive on Dangerous Substances (67/548/EEC): Possible risk of irreversible effects, (substances suspected of being carcinogenic and/or mutagenic)</p> <p>Exposure to the material for prolonged periods may cause physical defects in the developing embryo (teratogenesis).</p>   |
| <b>Megacryl S130 (Part B) &amp; ANILINE</b>              | <p>Exposure to the material may result in a possible risk of irreversible effects. The material may produce mutagenic effects in man. This concern is raised, generally, on the basis of appropriate studies using mammalian somatic cells <i>in vivo</i>. Such findings are often supported by positive results from <i>in vitro</i> mutagenicity studies.</p>   |
| <b>Megacryl S130 (Part B) &amp; METHYL METHACRYLATE</b>  | <p>Asthma-like symptoms may continue for months or even years after exposure to the material ends. This may be due to a non-allergic condition known as reactive airways dysfunction syndrome (RADS) which can occur after exposure to high levels of highly irritating compound. Main criteria for diagnosing RADS include the absence of previous airways disease in a non-atopic individual, with sudden onset of persistent asthma-like symptoms within minutes to hours of a documented exposure to the irritant. Other criteria for diagnosis of RADS include a reversible airflow pattern on lung function tests, moderate to severe bronchial hyperreactivity on methacholine challenge testing, and the lack of minimal lymphocytic inflammation, without eosinophilia. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. On the other hand, industrial bronchitis is a disorder that occurs as a result of exposure due to high concentrations of irritating substance (often particles) and is completely reversible after exposure ceases. The disorder is characterized by difficulty breathing, cough and mucus production.</p> <p><b>For methyl methacrylate:</b></p> <p>Acute toxicity: MMA is rapidly absorbed after oral or inhalatory administration. <i>In vitro</i> skin absorption studies in human skin indicate that MMA can be absorbed through human skin. After inhalation to rats 10 to 20% of the substance is deposited in the upper respiratory tract where it is metabolised by local tissue esterases.</p> <p>Acute toxicity of MMA by the oral, dermal, and inhalative routes is low as judged by tests with different species: The oral LD50 for rats, mice, and rabbits is found to exceed 5000 mg/kg bw.</p> <p>Acute inhalation toxicity for rats and mice is described by LC50 values of &gt; 25 mg/l/4 hours.</p> <p>Acute dermal toxicity is reported for rabbits to exceed 5000 mg/kg bw. Skin and respiratory irritation are reported for subjects exposed to monomeric MMA. The substance has been shown to produce severe skin irritation when tested undiluted on rabbit skin. There are indications from studies in animals that MMA can be irritating to the respiratory system. In contact with eyes MMA has shown only weak irritation of the conjunctivae. MMA has a moderate to strong sensitising potential in experimental animals. Cases of contact dermatitis have been reported for workers exposed to the monomeric chemical. There is no convincing evidence that MMA is a respiratory sensitiser in humans.</p> <p>The lead effect caused by MMA is a degeneration of the olfactory region of the nose being the most sensitive target tissue. For this effect a NOAEC of 25 ppm (104 mg/m<sup>3</sup>) in a two-year inhalation study in rats was identified but only slight effects on the olfactory tissues have been observed at 100 ppm. Concerning systemic effects, two different valid studies have been considered for identifying a N(L)OAE. Due to different dose selections, different values for N(L)OELs are available. The LOELs and the NOELs for female rats ranges between 400 and 500 ppm and from 100 to 250 ppm respectively. In subchronic inhalation studies systemic toxic effects were seen in rats &gt;1000 ppm, respectively in mice &gt;500 ppm, including degenerative and necrotic lesions in liver, kidney, brain, and atrophic changes in spleen and bone marrow. These effects were not seen in chronic studies up to 1000 ppm. Oral administration to rats resulted in a NOAEL of 200 mg/kg bw/d.</p> <p>MMA has <i>in vitro</i> the potential for induction of mutagenic effects, especially clastogenicity. However, this potential is limited to high doses with strong toxic effects. Furthermore, the negative <i>in vivo</i> micronucleus test and the negative dominant lethal assay indicate that this potential is not expressed <i>in vivo</i>. There is no relevant concern on carcinogenicity of MMA in humans and animals. Epidemiology data on increased tumour rates in exposed cohorts are of limited reliability and cannot be related to MMA as the solely causal agent.</p> |

**Megacryl S130 (Part B)**

|   |  |
|---|--|
|   | MMA did not reveal an effect on male fertility when animals had been exposed to up to 9000 ppm. From the available developmental toxicity investigations, including an inhalation study according to OECD Guideline 414, no teratogenicity, embryotoxicity or fetotoxicity has been observed at exposure levels up to and including 2028 ppm (8425 mg/m3). The available human data on sexual disorders in male and female workers cannot be considered to conclude on reproductive toxicity effects of MMA due to the uncertain validity of the studies   |
| <b>Megacryl S130 (Part B) &amp; METHYL METHACRYLATE &amp; 3,5-DIETHYL-1,2-DIHYDRO-1-PHENYL-2-PROPYLPYRIDINE &amp; ANILINE</b> | The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact. From a clinical point of view, substances are noteworthy if they produce an allergic test reaction in more than 1% of the persons tested. |
| <b>METHYL METHACRYLATE &amp; ANILINE</b>  | The substance is classified by IARC as Group 3:<br><b>NOT</b> classifiable as to its carcinogenicity to humans.<br>Evidence of carcinogenicity may be inadequate or limited in animal testing.   |

|  |   |                                 |   |
|--|---|---------------------------------|---|
| <b>Acute Toxicity</b>                    | ✗ | <b>Carcinogenicity</b>          | ✗ |
| <b>Skin Irritation/Corrosion</b>         | ✓ | <b>Reproductivity</b>           | ✗ |
| <b>Serious Eye Damage/Irritation</b>     | ✓ | <b>STOT - Single Exposure</b>   | ✓ |
| <b>Respiratory or Skin sensitisation</b> | ✓ | <b>STOT - Repeated Exposure</b> | ✗ |
| <b>Mutagenicity</b>                      | ✓ | <b>Aspiration Hazard</b>        | ✗ |

**Legend:** ✗ – Data either not available or does not fill the criteria for classification  
✓ – Data available to make classification

**SECTION 12 Ecological information**

**Toxicity**

| <b>Megacryl S130 (Part B)</b>                            | <b>Endpoint</b> | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|--|-----------------|---------------------------|-------------------------------|---------------|---------------|
|  | Not Available   | Not Available             | Not Available                 | Not Available | Not Available |
| <b>methyl methacrylate</b>                               | <b>Endpoint</b> | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|  | EC50            | 72h                       | Algae or other aquatic plants | >110mg/l      | 2             |
|  | EC50            | 96h                       | Algae or other aquatic plants | 170mg/l       | 1             |
|  | EC50            | 48h                       | Crustacea                     | 69mg/l        | 1             |
|  | EC0(ECx)        | 48h                       | Crustacea                     | 48mg/l        | 1             |
|  | LC50            | 96h                       | Fish                          | >79mg/l       | 2             |
| <b>3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine</b> | <b>Endpoint</b> | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|  | Not Available   | Not Available             | Not Available                 | Not Available | Not Available |
| <b>cyclohexane</b>                                       | <b>Endpoint</b> | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|  | EC50            | 96h                       | Algae or other aquatic plants | 2.17mg/l      | 2             |
|  | BCF             | 1344h                     | Fish                          | 31-102        | 7             |
|  | EC50            | 72h                       | Algae or other aquatic plants | 3.428mg/l     | 2             |
|  | EC50(ECx)       | 48h                       | Crustacea                     | 0.9mg/l       | 2             |
|  | EC50            | 48h                       | Crustacea                     | 0.9mg/l       | 2             |
|  | LC50            | 96h                       | Fish                          | 4.53mg/l      | 2             |
| <b>aniline</b>   | <b>Endpoint</b> | <b>Test Duration (hr)</b> | <b>Species</b>                | <b>Value</b>  | <b>Source</b> |
|  | EC50            | 96h                       | Algae or other aquatic plants | 19mg/l        | 4             |
|  | EC50            | 72h                       | Algae or other aquatic plants | 10-32mg/L     | 4             |
|  | NOEC(ECx)       | 504h                      | Crustacea                     | 0.004mg/l     | 2             |
|  | LC50            | 96h                       | Fish                          | 5-7mg/l       | 2             |
|  | EC50            | 48h                       | Crustacea                     | 0.08-1mg/l    | 4             |

**Legend:** Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity 4. US EPA, Ecotox database - Aquatic Toxicity Data 5. ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) -

**Megacryl S130 (Part B)**

**Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8. Vendor Data**

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Do NOT allow product to come in contact with surface waters or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment wash-waters.

Wastes resulting from use of the product must be disposed of on site or at approved waste sites.

For methyl methacrylate (MMA):

Koc : 87

Half-life (hr) air : 2.7-3

Half-life (hr) H<sub>2</sub>O surface water : 6.3-336

Henry's atm m<sup>3</sup> /mol: 3.24E-04

BOD 5 0.14

log BCF : 0.55

**Environmental fate:**

MMA has a water solubility of 16 g/l, a vapour pressure of 42 hPa, and a log Pow of 1.83. The environmental behavior of MMA is determined by its range of 1.1 - 9.7 hours atmospheric half life and moderate volatility. MMA is readily biodegradable. Hydrolysis is not significant at neutral and acidic pH, but increases in the upper pH range. The average K<sub>p</sub> value of 1.0 l/kg indicates no relevant adsorption onto sediment or soil. Based on the physico-chemical properties of MMA, the air and to a much lower extent the hydrosphere are the preferred target compartments for distribution and neither relevant bioaccumulation nor geoaccumulation are expected. In waste water treatment plants 89.2 % of the substance are estimated to be removed predominately by biodegradation.

**Ecotoxicity:**

Fish LC<sub>50</sub> (96 h): *Lepomis macrochirus* 191 mg/l; rainbow trout (*Oncorhynchus mykiss*) >79 mg/l, NOEC 40 mg/l

*Daphnia magna* EC NOEC (21 d) 37 mg/l

*Daphnia magna* EC<sub>50</sub> (48 h): 69 mg/l

The most relevant study on algae has examined *Selenastrum capricornutum* according to OECD guideline 201. The highest test concentration of 110 mg/l caused growth inhibition below 50 %, the NOEC was 110 mg/l for growth rate and 49 mg/l for biomass as endpoints.

Based on these data there is a moderate hazard concern to aquatic organisms. For derivation of the Predicted No Effect Concentration (PNEC) the lowest valid effect concentration, i.e. 37 mg/l from the long-term daphnid test, is divided by an assessment factor of 50 as proposed in the TGD for the present data basis: PNEC<sub>aqua</sub> = 740 ug/l.

It is not possible to derive a PNEC for the atmospheric compartment due to the lack of experimental data.

Data on effects to terrestrial organisms are not available. In an indicative risk assessment for the soil compartment, the aquatic PNEC of 740 ug/l can be used and compared to the concentration in soil pore water.

Substances containing unsaturated carbons are ubiquitous in indoor environments. They result from many sources (see below). Most are reactive with environmental ozone and many produce stable products which are thought to adversely affect human health. The potential for surfaces in an enclosed space to facilitate reactions should be considered.

| Source of unsaturated substances   | Unsaturated substances (Reactive Emissions)  | Major Stable Products produced following reaction with ozone.   |
|--|--|---|
| Occupants (exhaled breath, ski oils, personal care products)                           | Isoprene, nitric oxide, squalene, unsaturated sterols, oleic acid and other unsaturated fatty acids, unsaturated oxidation products        | Methacrolein, methyl vinyl ketone, nitrogen dioxide, acetone, 6MHQ, geranyl acetone, 4OPA, formaldehyde, nonanol, decanal, 9-oxo-nonanoic acid, azelaic acid, nonanoic acid.  |
| Soft woods, wood flooring, including cypress, cedar and silver fir boards, houseplants | Isoprene, limonene, alpha-pinene, other terpenes and sesquiterpenes  | Formaldehyde, 4-AMC, pinoaldehyde, pinic acid, pinonic acid, formic acid, methacrolein, methyl vinyl ketone, SOAs including ultrafine particles   |
| Carpets and carpet backing   | 4-Phenylcyclohexene, 4-vinylcyclohexene, styrene, 2-ethylhexyl acrylate, unsaturated fatty acids and esters                                | Formaldehyde, acetaldehyde, benzaldehyde, hexanal, nonanal, 2-nonenal   |
| Linoleum and paints/polishes containing linseed oil                                    | Linoleic acid, linolenic acid  | Propanal, hexanal, nonanal, 2-heptenal, 2-nonenal, 2-decenal, 1-pentene-3-one, propionic acid, n-butyric acid   |
| Latex paint  | Residual monomers  | Formaldehyde  |
| Certain cleaning products, polishes, waxes, air fresheners                             | Limonene, alpha-pinene, terpinolene, alpha-terpineol, linalool, linalyl acetate and other terpenoids, longifolene and other sesquiterpenes | Formaldehyde, acetaldehyde, glycoaldehyde, formic acid, acetic acid, hydrogen and organic peroxides, acetone, benzaldehyde, 4-hydroxy-4-methyl-5-hexen-1-al, 5-ethenyl-dihydro-5-methyl-2(3H)-furanone, 4-AMC, SOAs including ultrafine particles |
| Natural rubber adhesive  | Isoprene, terpenes   | Formaldehyde, methacrolein, methyl vinyl ketone   |
| Photocopier toner, printed paper, styrene polymers                                     | Styrene  | Formaldehyde, benzaldehyde  |
| Environmental tobacco smoke  | Styrene, acrolein, nicotine  | Formaldehyde, benzaldehyde, hexanal, glyoxal, N-methylformamide, nicotinaldehyde, cotinine  |
| Soiled clothing, fabrics, bedding  | Squalene, unsaturated sterols, oleic acid and other saturated fatty acids  | Acetone, geranyl acetone, 6MHO, 4OPA, formaldehyde, nonanal, decanal, 9-oxo-nonanoic acid, azelaic acid, nonanoic acid  |
| Soiled particle filters  | Unsaturated fatty acids from plant waxes, leaf litter, and other vegetative debris; soot; diesel particles                                 | Formaldehyde, nonanal, and other aldehydes; azelaic acid; nonanoic acid; 9-oxo-nonanoic acid and other oxo-acids; compounds with mixed functional groups (=O, -OH, and -COOH)   |
| Ventilation ducts and duct liners  | Unsaturated fatty acids and esters, unsaturated oils, neoprene   | C5 to C10 aldehydes   |
| "Urban grime"  | Polycyclic aromatic hydrocarbons   | Oxidized polycyclic aromatic hydrocarbons   |
| Perfumes, colognes, essential oils (e.g. lavender, eucalyptus, tea tree)               | Limonene, alpha-pinene, linalool, linalyl acetate, terpinene-4-ol, gamma-terpinene   | Formaldehyde, 4-AMC, acetone, 4-hydroxy-4-methyl-5-hexen-1-al, 5-ethenyl-dihydro-5-methyl-2(3H) furanone, SOAs including ultrafine particles  |
| Overall home emissions   | Limonene, alpha-pinene, styrene  | Formaldehyde, 4-AMC, pinonaldehyde, acetone, pinic acid, pinonic acid, formic acid, benzaldehyde, SOAs including ultrafine particles  |

Abbreviations: 4-AMC, 4-acetyl-1-methylcyclohexene; 6MHQ, 6-methyl-5-heptene-2-one, 4OPA, 4-oxopentanal, SOA, Secondary Organic Aerosols

Reference: Charles J Weschler; Environmental Health Perspectives, Vol 114, October 2006

**DO NOT discharge into sewer or waterways.**

**Persistence and degradability**

| Ingredient  | Persistence: Water/Soil     | Persistence: Air            |
|---|-----------------------------|-----------------------------|
| methyl methacrylate                               | LOW                         | LOW                         |
| 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine | HIGH                        | HIGH                        |
| cyclohexane                                       | HIGH (Half-life = 360 days) | LOW (Half-life = 3.63 days) |
| aniline   | HIGH                        | HIGH                        |

Bioaccumulative potential

| Ingredient  | Bioaccumulation      |
|---|----------------------|
| methyl methacrylate                               | LOW (BCF = 6.6)      |
| 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine | HIGH (LogKOW = 6.58) |
| cyclohexane                                       | LOW (BCF = 242)      |
| aniline   | LOW (LogKOW = 0.9)   |

Mobility in soil

| Ingredient  | Mobility              |
|---|-----------------------|
| methyl methacrylate                               | LOW (Log KOC = 10.14) |
| 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine | LOW (Log KOC = 34730) |
| cyclohexane                                       | LOW (Log KOC = 165.5) |
| aniline   | LOW (Log KOC = 44.78) |

SECTION 13 Disposal considerations

Waste treatment methods

|                              |   |
|------------------------------|---|
| Product / Packaging disposal | <ul style="list-style-type: none"><li>Containers may still present a chemical hazard/ danger when empty.</li><li>Return to supplier for reuse/ recycling if possible.</li></ul> Otherwise: <ul style="list-style-type: none"><li>If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li><li>Where possible retain label warnings and SDS and observe all notices pertaining to the product.</li></ul> Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.<br>A Hierarchy of Controls seems to be common - the user should investigate: <ul style="list-style-type: none"><li>Reduction</li><li>Reuse</li><li>Recycling</li><li>Disposal (if all else fails)</li></ul> This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate. <ul style="list-style-type: none"><li><b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li><li>It may be necessary to collect all wash water for treatment before disposal.</li><li>In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.</li><li>Where in doubt contact the responsible authority.</li><li>Recycle wherever possible.</li><li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li><li>Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li><li>Decontaminate empty containers. Observe all label safeguards until containers are cleaned and destroyed.</li></ul> |
|------------------------------|---|

SECTION 14 Transport information

Labels Required

|  |   |
|--|---|
|  |  |
|--|---|

Megacryl S130 (Part B)

|                  |   |
|------------------|---|
| Marine Pollutant |  |
| HAZCHEM          | •3YE  |

Land transport (ADG)

|                                    |                                       |                |
|------------------------------------|---------------------------------------|----------------|
| 14.1. UN number or ID number       | 1133                                  |                |
| 14.2. UN proper shipping name      | ADHESIVES containing flammable liquid |                |
| 14.3. Transport hazard class(es)   | Class                                 | 3              |
|                                    | Subsidiary Hazard                     | Not Applicable |
| 14.4. Packing group                | II                                    |                |
| 14.5. Environmental hazard         | Environmentally hazardous             |                |
| 14.6. Special precautions for user | Special provisions                    | Not Applicable |
|                                    | Limited quantity                      | 5 L            |

Air transport (ICAO-IATA / DGR)

|                                    |   |                |
|------------------------------------|---|----------------|
| 14.1. UN number                    | 1133  |                |
| 14.2. UN proper shipping name      | Adhesives containing flammable liquid                     |                |
| 14.3. Transport hazard class(es)   | ICAO/IATA Class   | 3              |
|                                    | ICAO / IATA Subsidiary Hazard                             | Not Applicable |
|                                    | ERG Code  | 3L             |
| 14.4. Packing group                | II  |                |
| 14.5. Environmental hazard         | Environmentally hazardous                                 |                |
| 14.6. Special precautions for user | Special provisions  | A3             |
|                                    | Cargo Only Packing Instructions                           | 364            |
|                                    | Cargo Only Maximum Qty / Pack                             | 60 L           |
|                                    | Passenger and Cargo Packing Instructions                  | 353            |
|                                    | Passenger and Cargo Maximum Qty / Pack                    | 5 L            |
|                                    | Passenger and Cargo Limited Quantity Packing Instructions | Y341           |
|                                    | Passenger and Cargo Limited Maximum Qty / Pack            | 1 L            |

Sea transport (IMDG-Code / GGVSee)

|                                    |                                       |                |
|------------------------------------|---------------------------------------|----------------|
| 14.1. UN number                    | 1133                                  |                |
| 14.2. UN proper shipping name      | ADHESIVES containing flammable liquid |                |
| 14.3. Transport hazard class(es)   | IMDG Class                            | 3              |
|                                    | IMDG Subsidiary Hazard                | Not Applicable |
| 14.4. Packing group                | II                                    |                |
| 14.5. Environmental hazard         | Marine Pollutant                      |                |
| 14.6. Special precautions for user | EMS Number                            | F-E , S-D      |
|                                    | Special provisions                    | Not Applicable |
|                                    | Limited Quantities                    | 5 L            |

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable



**Megacryl S130 (Part B)**

**14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code**

| Product name                                      | Group         |
|---|---------------|
| methyl methacrylate                               | Not Available |
| 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine | Not Available |
| cyclohexane                                       | Not Available |
| aniline   | Not Available |

**14.7.3. Transport in bulk in accordance with the IGC Code**

| Product name                                      | Ship Type     |
|---|---------------|
| methyl methacrylate                               | Not Available |
| 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine | Not Available |
| cyclohexane                                       | Not Available |
| aniline   | Not Available |

**SECTION 15 Regulatory information**

**Safety, health and environmental regulations / legislation specific for the substance or mixture**

**methyl methacrylate is found on the following regulatory lists**

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 10 / Appendix C
- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
- Australian Inventory of Industrial Chemicals (AIIC)
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

**3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine is found on the following regulatory lists**

- Australian Inventory of Industrial Chemicals (AIIC)

**cyclohexane is found on the following regulatory lists**

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australian Inventory of Industrial Chemicals (AIIC)

**aniline is found on the following regulatory lists**

- Australia Hazardous Chemical Information System (HCIS) - Hazardous Chemicals
- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 5
- Australia Standard for the Uniform Scheduling of Medicines and Poisons (SUSMP) - Schedule 6
- Australian Inventory of Industrial Chemicals (AIIC)
- Chemical Footprint Project - Chemicals of High Concern List
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs
- International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Group 2A: Probably carcinogenic to humans

**Additional Regulatory Information**

Not Applicable

**National Inventory Status**

| National Inventory                              | Status  |
|---|---|
| Australia - AIIC / Australia Non-Industrial Use | Yes   |
| Canada - DSL                                    | Yes   |
| Canada - NDSL                                   | No (methyl methacrylate; 3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine; cyclohexane; aniline) |
| China - IECSC                                   | Yes   |
| Europe - EINEC / ELINCS / NLP                   | Yes   |
| Japan - ENCS                                    | No (3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine)  |
| Korea - KECI                                    | Yes   |
| New Zealand - NZIoC                             | Yes   |
| Philippines - PICCS                             | Yes   |
| USA - TSCA                                      | All chemical substances in this product have been designated as TSCA Inventory 'Active'           |

Megacryl S130 (Part B)

| National Inventory | Status  |
|--------------------|---|
| Taiwan - TCSI      | Yes   |
| Mexico - INSQ      | No (3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine)  |
| Vietnam - NCI      | Yes   |
| Russia - FBEPH     | No (3,5-diethyl-1,2-dihydro-1-phenyl-2-propylpyridine)  |
| Legend:            | Yes = All CAS declared ingredients are on the inventory<br>No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration. |

SECTION 16 Other information

|               |            |
|---------------|------------|
| Revision Date | 09/01/2025 |
| Initial Date  | 09/01/2025 |

Other information

Ingredients with multiple cas numbers

| Name    | CAS No   |
|---------|--|
| aniline | 62-53-3, 146997-94-6, 1533423-51-6, 1582784-51-7, 1619933-02-6, 37342-16-8 |

Classification of the preparation and its individual components has drawn on official and authoritative sources using available literature references. The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

Definitions and abbreviations

- PC - TWA: Permissible Concentration-Time Weighted Average
- PC - STEL: Permissible Concentration-Short Term Exposure Limit
- IARC: International Agency for Research on Cancer
- ACGIH: American Conference of Governmental Industrial Hygienists
- STEL: Short Term Exposure Limit
- TEEL: Temporary Emergency Exposure Limit,
- IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- MARPOL: International Convention for the Prevention of Pollution from Ships
- IMSBC: International Maritime Solid Bulk Cargoes Code
- IGC: International Gas Carrier Code
- IBC: International Bulk Chemical Code
  
- AIIC: Australian Inventory of Industrial Chemicals
- DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- IECSC: Inventory of Existing Chemical Substance in China
- EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
- NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- TSCA: Toxic Substances Control Act
- TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances